162-WP-004-001

HDF-EOS Interface Based on HDF5, Volume 1: Overview and Examples

White Paper

White paper - Not intended for formal review or Government approval.

December 1999

Prepared Under Contract NAS5-60000


RESPONSIBLE ENGINEER

Larry Klein /s/	12-16-99	9
David Wynne, Alex Muslimov,	Abe Taaheri,	Date
Ray Milburn, Larry Klein		
EOSDIS Core System Project		

SUBMITTED BY

Robert Plante /s/	12-16-99
Robert Plante, Manager, Science Office	Date
EOSDIS Core System Project	

Raytheon Systems Company Upper Marlboro, Maryland



Preface

This document is a Users Guide for HDF-EOS (Hierarchical Data Format - Earth Observing System) library tools. The version described in this document is HDF-EOS Version 3.0. The software is based on HDF5, a new version of HDF provided by NCSA. HDF5 is a complete rewrite of the earlier HDF4 version, containing a different data model and user interface. HDF-EOS V3.0 incorporates HDF5, and keeps the familier HDF4-based interface, There are a few exceptions and these exceptions are described in this document. Note that the contents of this document describe a prototype library, which is not yet operational. Release of an operational version is subject to NASA approval, but is expected in the summer of 2000.

HDF is the scientific data format standard selected by NASA as the baseline standard for EOS. This Users Guide accompanies Version 3 software, which is available to the user community on the EDHS1 server. This library is aimed at EOS data producers and consumers, who will develop their data into increasingly higher order products. These products range from calibrated Level 1 to Level 4 model data. The primary use of the HDF-EOS library will be to create structures for associating geolocation data with their associated science data. This association is specified by producers through use of the supplied library. Most EOS data products which have been identified, fall into categories of point, grid or swath structures, the latter two of which are implemented in the current version of the library. Services based on geolocation information will be built on HDF-EOS structures. Producers of products not covered by these structures, e.g. non-geolocated data, can use the standard HDF libraries.

In the ECS (EOS Core System) production system, the HDF-EOS library will be used in conjunction with SDP (Science Data Processing) Toolkit software. The primary tools used in conjunction with HDF-EOS library will be those for metadata handling, process control and status message handling. Metadata tools will be used to write ECS inventory and granule specific metadata into HDF-EOS files, while the process control tools will be used to access physical file handles used by the HDF tools. (SDP Toolkit Users Guide for the ECS Project, June 1999, 333-CD-500-001).

HDF-EOS is an extension of NCSA (National Center for Supercomputing Applications) HDF and uses HDF library calls as an underlying basis. Version 5-1.2.0 of HDF is used. The library tools are written in the C language and a FORTRAN interface is provided. The current version contains software for creating, accessing and manipulating Grid and Swath structures. This document includes overviews of the interfaces, and code examples. EOSView, the HDF-EOS viewing tool, has been revised to accommodate the current version of the library.

Technical Points of Contact within EOS are:

Larry Klein, larry@eos.hitc.com David Wynne, davidw@eos.hitc.com An email address has been provided for user help: pgstlkit@eos.hitc.com

Any questions should be addressed to:

Data Management Office The ECS Project Office Raytheon Systems Company 1616 McCormick Drive Upper Marlboro, MD 20774-5301

Abstract

This document will serve as the user's guide to the prototype HDF-EOS file access library based on HDF5. HDF refers to the scientific data format standard selected by NASA as the baseline standard for EOS, and HDF-EOS refers to EOS conventions for using HDF. This document will provide information on the use of the two interfaces included in this version – Swath, and Grid – including overviews of the interfaces, and code examples. This document should be suitable for use by data producers and data users alike.

Keywords: HDF-EOS, HDF5, Metadata, Standard Data Format, Standard Data Product, Disk Format, Grid, Swath, Projection, Array, Browse

This page intentionally left blank.

Contents

Preface

Abstract

1. Introduction

1.1	Identification	1-1
1.2	Scope	1-1
1.3	Purpose and Objectives	1-1
1.4	Status and Schedule	1-2
1.5	Document Organization	1-2
	2. Related Documentation	
2.1	Parent Documents	2-1
2.2	Related Documents	2-1
	3. Overview of HDF-EOS	
3.1	Background	3-1
3.2	Design Philosophy	3-1
3.3	Packaging	3-2
3.4	Operations Concept for the HDF5 Based Prototype Library	3-3
3.5	Differences Between HDF-EOS V2.5 (HDF4 based) and HDF-EOS V3.0 (HDF5 based)	3-3

4. Swath Data

4.1	Introduction		4-1
	4.1.1	Data Fields	4-2
	4.1.2	Geolocation Fields	4-3
	4.1.3	Dimensions	4-3
	4.1.4	Dimension Maps.	4-3
	4.1.5	Index	4-5
4.2	Applica	bility	4-5
4.3	The Swa	ath Data Interface	4-5
	4.3.1	SW API Routines	4-5
	4.3.2	File Identifiers	4-7
	4.3.3	Swath Identifiers.	4-7
4.4	Program	nming Model	4-7
		5. Grid Data	
5.1	Introduc	ction	5-1
	5.1.1	Data Fields	5-2
	5.1.2	Dimensions	5-2
	5.1.3	Projections	5-2
5.2	Applica	bility	5-3
5.3	The Gri	d Data Interface	5-3
	5.3.1	GD API Routines	5-3
	5.3.2	File Identifiers	5-5
	5.3.3	Grid Identifiers.	5-5
5.4	Program	nming Model	5-5
5.5	GCTP U	Jsage	5-6
	5.5.1	GCTP Projection Codes	5-6
	5.5.2	UTM Zone Codes	5-7
	5.5.3	GCTP Spheroid Codes	5-8
	5.5.4	Projection Parameters	5-9

6. Examples of HDF-EOS Library Usage

6.1	Swath E	Examples6-1
	6.1.1	Creating a Simple Swath6-1
	6.1.2	Performing Subsetting for a Swath
6.2	Grid Ex	amples6-20
	6.2.1	Creating a Simple Grid6-20
	6.2.2	Performing Subsetting for a Grid
6.3	Combin	ing HDF and HDF-EOS Objects6-47
	6.3.1	Adding HDF-EOS Structures to an Existing HDF File6-47
		7. Writing ODL Metadata into HDF-EOS
7.1	A C Exa	ample of Metadata Write7-1
7.2	C Code	7-1
7.3	The Me	tadata Configuration File (MCF) for Code in Section 7.2
7.4	The OD	L Ouput File Which Results from Running
7.5	The file	filetable.temp used for example in Section 7.2
		Appendix A. Installation and Maintenance
		List of Figures
4-1.	A Typic	al Satellite Swath: Scanning Instrument4-1
4-2.	A Swath	Derived from a Profiling Instrument4-2
4-3.	A "Norn	nal" Dimension Map4-4
4-4.	A "Back	wards" Dimension Map4-4
5-1.	A Data I	Field in a Mercator-projected Grid5-1
5-2.	A Data I	Field in an Interrupted Goode's Homolosine-Projected Grid5-2

List of Tables

3-1.	HDF-EOS 3.0 (Prototype) Current Modifications to the HDF4-Based HDF-EOS Library (2.5)	3-4
4-1.	Summary of the Swath Interface	4-6
5-1.	Summary of the Grid Interface	5-4
5-2.	Projection Transformation Package Projection Parameters	5-9
5-3.	Projection Transformation Package Projection Parameters Elements	5-10

Abbreviations and Acronyms

1. Introduction

1.1 Identification

The *HDF-EOS User's Guide for the ECS Project* was prepared under the Earth Observing System Data and Information System (EOSDIS) Core System (ECS), Contract (NAS5-60000).

1.2 Scope

This document is intended for use by anyone who wishes to write software to create or read EOS data products. Users of this document will likely include EOS instrument team science software developers and data product designers, DAAC personnel, and end users of EOS data products such as scientists and researchers.

Note: This current document describes a prototype library based on HDF5. Official NASA support of this new data format is not yet at hand. This recognition is expected in early 2000. In the near term, an HDF-EOS interface for both HDF4 and HDF5 based files will be provided. The HDF4 based library is currently V2.5.

1.3 Purpose and Objectives

This document will serve as a user's guide for the HDF-EOS file access library developed for ECS. Upon reading this document, the reader should have a thorough understanding of each data model and corresponding programming interface provided as part of HDF-EOS. Specifically, this user's guide contains an overview of each data model, a complete function-by-function reference for each software interface, and sample programs illustrating the basic features of each interface.

The reader should note that this paper will not discuss the HDF structures underlying HDF-EOS nor the specific conventions employed. For more information on HDF, its design philosophy, and its logical and physical formats, the reader is referred to NCSA documentation listed in Section 2.2 Applicable Documents. For more information on the conventions employed by HDF-EOS, the reader is referred to the various design White Papers listed in Section 2.2.

Important Note:

The FORTRAN-literate reader is cautioned that dimension ordering is row-major in C (last dimension varying fastest), whereas FORTRAN uses column-major ordering (first dimension varying fastest). Therefore, FORTRAN programmers should take care to use dimensions in the reverse order to that shown in the text of this document. (FORTRAN code examples are correct as written.)

1-1

1.4 Status and Schedule

December, 1999, Prototype HDF5 based Library Available

August, 2000, SCF version including both HDF4 and HDF5 support available.

June, 2001, ECS support available.

Note that this schedule is proposed to NASA, but not yet accepted at the time of this writing.

1.5 Document Organization

This document is organized as follows:

- Section 1 Introduction Presents Scope and Purpose of this document
- Section 2 Related Documentation
- Section 3 Overview of HDF-EOS Background and design features of the library.
- Section 4 Swath Data Design features and listing of the HDF-EOS Swath Library.
- Section 6 Grid Data Design features and listing of the HDF-EOS Grid Library.
- Section 7 Examples A selection of programming examples.
- Section 8. Examples of SDP Toolkit Usage How to use the HDF-EOS Library in conjunction with the SDP Toolkit.
- Appendix A Installation Instructions, Test Drivers, User Feedback
- Acronyms

The accompanying Function Reference Guide is organized as follows:

- Section 1 Introduction
- Section 2 Reference Specification of the HDF-EOS Swath and Grid
- APIs Function
- Acronyms

2. Related Documentation

2.1 Parent Documents

The following documents are the parents from which this document's scope and content derive:

170-TP-500□	The HDF-EOS Library Users Guide for the ECS Project, Volume 1:Overview and Examples
170-TP-501□	The HDF-EOS Library Users Guide for the ECS Project, Volume 2: Function Reference Guide
456-TP-013	The HDF-EOS Design Document for the ECS Project
170-WP-002	Thoughts on HDF-EOS Metadata, A White Paper for the ECS Project
170-WP-003	The HDF-EOS Swath Concept, A White Paper for the ECS Project
170-WP-011	The HDF-EOS Grid Concept, A White Paper for the ECS Project

2.2 Related Documents

The following documents are referenced within this technical paper, or are directly applicable, or contain policies or other directive matters that are binding upon the content of this document.

333-CD-003	Release A SCF Toolkit Users Guide for the ECS Project
163-WP-001□	An ECS Data Provider's Guide to Metadata in Release A, A White Paper for the ECS Project
175-WP-001□	HDF-EOS Primer for Version 1 EOSDIS, A White Paper for the ECS Project
none	Introduction to HDF5 Release 1.2, University of Illinois, October, 1999
none	HDF5: API Specification Reference Manual, October, 1999
none	Getting Started with HDF, Version 3.2, University of Illinois, May 1993
none	NCSA HDF Reference Manual, Version 3.3, University of Illinois, February 1994
none	NCSA HDF Specification and Developer's Guide, Version 3.2, University of Illinois, September 1993
none	NCSA HDF User's Guide, Version 4.0, University of Illinois, February 1996

none NCSA HDF User's Guide, Version 3.3, University of Illinois, March

1994

none An Album of Map Projections, USGS Professional Paper 1453, Snyder

and Voxland, 1989

none Map Projections - A Working Manual, USGS Professional Paper 1395,

Snyder, 1987

none The WMO Format for the Storage of Weather Product Information and

the Exchange of Weather Product Messages in Gridded Binary Form, John D. Stackpole, Office Note 388, GRIB Edition 1, U.S. Dept. of

Commerce, NOAA, National Weather Service National

Meteorological Center, Automation Division, Section 1, pp. 9-12, July

1, 1994.

none The Michigan Earth Grid: Description, Registration Method for SSM/I

Data, and Derivative Map Projection, John F. Galntowicz, Anthony W. England, The University of Michigan, Radiation Laborartory, Ann

Arbor, Michigan, Feb. 1991.

none Selection of a Map Grid for Data Analysis and Archiva, William B.

Rossow, and Leonid Garder, American Meteorological Society Notes,

pp. 1253-1257, Aug. 1984.

none Level-3 SeaWiFS Data Products: Spatial and Temporal Binning

Algorithms, Janet W. Campbell, John M. Blaisdell, and Michael Darzi, NASA Technical Memorandum 104566, GSFC, Volume 32, Appendix

A, Jan. 13, 1995.

3. Overview of HDF-EOS

3.1 Background

The Hierarchical Data Format (HDF) has been selected by the EOSDIS Project as the format of choice for standard product distribution. HDF is a function library that was originally developed by the National Center for Supercomputing Applications (NCSA) at the University of Illinois at Urbana-Champaign to provide a portable storage mechanism for supercomputer simulation results. Although this user's guide does not attempt to explain the inner workings of NCSA HDF, a cursory knowledge of HDF may help the reader to understand the basic workings of HDF-EOS.

HDF5 files consist of a directory and a collection of data objects. Every data object has a directory entry, containing a pointer to the data object location, and information defining the datatype (much more information about HDF can be found in the NCSA documentation referenced in Section 2.2 of this Guide). Unlike HDF4, there are only two fundamental data objects in HDF5. These objects are groups and dataspaces. The HDF4 data types such as vdatas and scientific data sets are mapped into the more general class of dataspaces.

To bridge the gap between the needs of EOS data products and the capabilities of HDF, three new EOS specific datatypes – *point*, *swath*, and *grid* – have been defined within the HDF framework. Each of these new datatypes is constructed using conventions for combining standard HDF datatypes and is supported by a special application programming interface (API) which aids the data product user or producer in the application of the conventions. The APIs allow data products to be created and manipulated in ways appropriate to each datatype, without regard to the actual HDF objects and conventions underlying them.

The sum of these new APIs comprise the HDF-EOS library. The *Point* interface is designed to support data that has associated geolocation information, but is not organized in any well defined spatial or temporal way. The *Swath* interface is tailored to support time-ordered data such as satellite swaths (which consist of a time-ordered series of scanlines), or profilers (which consist of a time-ordered series of profiles). The *Grid* interface is designed to support data that has been stored in a rectilinear array based on a well defined and explicitly supported projection.

Note that in this current protoype version, the Point interface is not implemented.

3.2 Design Philosophy

Since the HDF-EOS library is intended to support end users of EOS data as well as EOS data producers, it is essential that HDF-EOS be available separately from other ECS software. For this reason, HDF-EOS does not rely on any other ECS software, including the SDP Toolkit. It is treated as an extension to the HDF library and, as such, it follows the general design philosophy and coding style of HDF. For more information on the design of HDF, please refer to the appropriate NCSA documentation listed in Section 2.2.

3.3 Packaging

Because of the functional overlap of HDF, HDF-EOS, and the SDP Toolkit, it is important to understand what each one contains and how they are related. NCSA HDF is a subroutine library freely available as source code from the National Center for Supercomputing Applications. The basic HDF library has its own documentation, and comes with a selection of simple utilities.

HDF-EOS is a higher level library available from the ECS project as an add-on to the basic HDF library. It requires NCSA HDF for successful compiling and linking and will be widely available (at no charge) to all interested parties. Although at the time of this writing, the exact packaging has yet to be determined, the basic HDF library will also be available from the ECS project.

The SDP Toolkit is a large, complex library of functions for use by EOS data producers. It presents a standard interface to Distributed Active Archive Center (DAAC) services for data processing, job scheduling, and error handling. While the SDP Toolkit may be available to individual researchers, it is unlikely to be of great use outside of EOS DAACs and Science Computing Facilities (SCF). The Toolkit distribution includes source code for both HDF and HDF-EOS.

EOS instrument data producers will use the SDP Toolkit in conjunction with the HDF-EOS and HDF libraries. Of primary importance will be process control and metadata handling tools. The former will be used to access physical file handles required by the HDF library. The SDP Toolkit uses logical file handles to access data, while HDF (HDF-EOS) requires physical handles. Users will be required to make one additional call, using the SDP toolkit to access the physical handles. Please refer to the SDP Toolkit Users Guide for the ECS Project, Mar, 1998, 333-CD-100-001, Section 6.2.1.2 for an example). Section 7 of this document gives examples of HDF-EOS usage in conjunction with the SDP Toolkit.

Metadata tools will be used to access and write inventory and granule specific metadata into their designated HDF structures. Please refer to Section 6.2.1.4 of the SDP Toolkit Users Guide.

Note that in this current prototype, only read and write metadata functions have been implemented to use HDF5 based files.

We make an important distinction between granule metadata and the structural metadata referred to in the software description below. Structural metadata specifies the internal HDF-EOS file structure and the relationship between geolocation data and the data itself. Structural metadata is created and then accessed by calling the HDF-EOS functions. Granule metadata will be used by ECS to perform archival services on the data. A copy will attached to HDF-EOS files by SDP toolkit calls and another copy is placed in the ECS archives. The two sets of metadata are not dynamically linked. However, the data producer should use consistent naming conventions when writing granule metadata when calling the HDF-EOS API. Please refer to the examples in Section 7, below.

3.4 Operations Concept for the HDF5 Based Prototype Library

HDF5 is a nearly complete rewrite of HDF4 and contains a different user API and underlying data model. An HDF-EOS library written in conjunction with HDF5 and which uses HDF5 functionality, will necessarily be a rewrite of the HDF4 - based version. The new HDF5 - based library will support the same Grid/Point/Swath functionality and to the extent possible and will be built with the same calling sequences as the original library. We will refer to the newer library as HDF-EOS 3.0. The former library is currently designated HDF-EOS 2.5. (The HDF-EOS Library Users Guide for the ECS Project, Volume 1 and Volume 2)

The following future uses for HDF-EOS are anticipated:

- A. Product developers reading and writing HDF4 based files.
- B. ECS subsystems reading and writing HDF4 based files.
- C. Product developers reading and writing HDF5 based files. This will include both users retrofitting HDF4-based software and users starting from scratch with HDF5.
- D. ECS subsystems reading and writing HDF5 based files.
- E. Data migration applications, i.e. read HDF4 and write HDF5.

HDF-EOS 3.0 support for HDF5 will have the same function calls as the current HDF-EOS 2.5 support for HDF4. There will be a few additions, such as calls to account for HDF5 implementation of ragged arrays. The parameters in the V3.0 function calls will be the same, to the extent possible. The name of the function calls will be the same. This implementation will entail the fewest possible modifications with respect to retrofitting code, i.e. removing HDF4 file access in favor of HDF5 file access. Users retrofitting old code, should anticipate changing variable types to accommodate new HDF5 variable types. The API will make the underlying HDF5 data model transparent otherwise.

If a user outside ECS wants to be able to read HDF4 files and write HDF5 files, we recommend using C++ class libraries. In that way, HDF4 and HDF5 based function names can remain the same. Another method will be to provide a parallel HDF5 based library in which function names have been changed. For example, SWopen() becomes SWopen5(). We will provide installation scripts, which will install HDF4 and/or HDF5 - based libraries based on user preference. This parallel library is not implemented in the prototype.

Support will be provided for the current suite of UNIX and Windows operating systems. F77, F90, C and C++ interfaces will continue to be supported.

3.5 Differences Between HDF-EOS V2.5 (HDF4 based) and HDF-EOS V3.0 (HDF5 based)

There are several important differences between the Versions 2.5 and 3.0 of the HDF-EOS library that are briefly summarized in this section. An overview of modifications to the HDF4 base library is listed in Table 3.1

Table 3-1. HDF-EOS 3.0 (Prototype) Current Modifications to the HDF4-Based HDF-EOS Library (2.5)

Function	ction Change Description				
Swath Access	Modify to implement new HDF5 file structure.				
	Create a swath with a specified name				
Swath Definition	Add an additional parameter, 'maxdimlist', a list of maximum sizes of dimensions. This will account for feature of appendibility of each dimension in a dataset.				
	Add a new function for chunking in HDF5 (SWdefchunk())				
Swath Inquiry	No new functionality or interface changes.				
Swath Input/output	 Add unsigned long type to store large number of elements in attributes. Change 'start,stride, edge' parameter type to allow for very large numbers. 				
Swath Subset	No new functionality or interface changes.				
New interfaces	 SWinqdatatype() retrieve information about data type of a data field SWraopen(),SWraread(),SWrawrite(), SWraclose() - Support HDF5 ragged array structures. 				
Grid Access	 Modify to implement new HDF5 file structure. Create a grid with a specified name 				
Grid Definition	 GDdeffield() modified to add 'maxdimlist', a comma separated list of maximum dimensions - same as for Swath Modify functions to support HDF5 chunking: GDdeftile() and GDdefcomp() and GDdefchunk(). 				
Grid Input/Output	Add unsigned long type to store large number of elements in attributes.				
Grid Inquiry	No new functionality or interface changes				
Grid Subset	No new functionality or interface changes				
Grid Tiling	No new functionality or interface changes				
Utilities	Add function for determining whether a file is HDF4 or HDF5 based.				
EOSView	Modified to accommodate new HDF5-based HDF-EOS library. This is a new tool				
	 which will compliment the original HDF4 - based tool. Removed HDF4 support. Added about 200 lines of code for HDF5 support. 				

Selected user considerations are listed below.

The routines SWopen(), SWcreate(), GDopen(), GDcreate() implement a new file structure designed for the V3.0 of the HDF-EOS library.

The field definition routines, SWdefgeofield(), SWdefdatafield(), and GDdeffield(), have an additional parameter 'maxdimlist', a coma separated list of maximum sizes of dimensions. The parameter 'maxdimlist' is reserved for future use. Since in HDF5 each dimension of a dataset can be appendable (extendible), the definition of a dataset should include the maximum size (or unlimited size) the corresponding dimension can be expanded to. Passing a NULL as a 'maxdimlist' means that the dimension is not appendable, and its maximum size is the same as its actual size. The unlimited dimension can be specified e.g by a call to SWdefdim(sw_id,

"Unlim",H5S_UNLIMITED). Then, in the call to e.g. SWdefdatafield() we should use for the 'maxdimlist' parameter the value "Unlim".

HDF5 requires the user to use chunking in order to define extendible datasets. Chunking makes it possible to extend datasets efficiently, without having to reorganize storage excessively. The corresponding (new) calls are SWdefchunk() and GDdeftile(). These calls should be used before the familiar old-library call to SWdefcomp() and GDdefcomp(), respectively. The latter set the field compression for all subsequent field definitions.

In the input/output routines SWwriteattr() and GDwriteattr(), the data type of the fourth parameter, number of values to store in attribute, is now such that it allows to store arbitrary big number of elements in attribute. Also, the routines SWwritefield(), SWreadfield(), GDwritefield(), and GDreadfield() allow for the parameters 'start', 'stride', and 'edge' to use very big numbers.

There are two new inquiry routines SWinqdatatype() and GDinqdatatype() that, for a specified field, retrieve explicit information about data type, including number of bytes allocated for each element of the corresponding dataset.

The following ragged array routines have been added for the swath interface:

SWradefine() - sets up the ragged array within the swath under the "Data Fields" group

SWraopen() - opens up a specified ragged array

SWrawrite() - writes in the data to a specified ragged array

SWraread() - reads out the data from a specified ragged array

SWraclose() - closes the ragged array

This page intentionally left blank.

4. Swath Data

4.1 Introduction

The Swath concept for HDF-EOS is based on a typical satellite swath, where an instrument takes a series of scans perpendicular to the ground track of the satellite as it moves along that ground track. Figure 4-1 below shows this traditional view of a swath.




Figure 4-1. A Typical Satellite Swath: Scanning Instrument

Another type of data that the Swath is equally well suited to arises from a sensor that measures a vertical profile, instead of scanning across the ground track. The resulting data resembles a standard Swath tipped up on its edge. Figure 4-1 shows how such a Swath might look.

In fact, the two approaches shown in Figures 4-1 and 4-2 can be combined to manage a profiling instrument that scans across the ground track. The result would be a three dimensional array of measurements where two of the dimensions correspond to the standard scanning dimensions (along the ground track and across the ground track), and the third dimension represents a height above the Earth or a range from the sensor. The "horizontal" dimensions can be handled as normal geographic dimensions, while the third dimension can be handled as a special "vertical" dimension.




Figure 4-2. A Swath Derived from a Profiling Instrument

A standard Swath is made up of four primary parts: data fields, geolocation fields, dimensions, and dimension maps. An optional fifth part called an index can be added to support certain kinds of access to Swath data. Each of the parts of a Swath is described in detail in the following subsections.

4.1.1 Data Fields

Data fields are the main part of a Swath from a science perspective. Data fields usually contain the raw data (often as *counts*) taken by the sensor or parameters derived from that data on a value-for-value basis. All the other parts of the Swath exist to provide information about the data fields or to support particular types of access to them. Data fields typically are two-dimensional arrays, but can have as few as one dimension or as many as eight, in the current library implementation. They can have any valid C data type.

4.1.2 Geolocation Fields

Geolocation fields allow the Swath to be accurately tied to particular points on the Earth's surface. To do this, the Swath interface requires the presence of at least a time field ("Time") or a latitude/longitude field pair ("Latitude" and "Longitude"). Geolocation fields must be either one- or two-dimensional and can have any data type.

4.1.3 Dimensions

Dimensions define the axes of the data and geolocation fields by giving them names and sizes. In using the library, dimensions must be defined before they can be used to describe data or geolocation fields.

Every axis of every data or geolocation field, then, must have a dimension associated with it. However, there is no requirement that they all be unique. In other words, different data and geolocation fields may share the same named dimension. In fact, sharing dimension names allows the Swath interface to make some assumptions about the data and geolocation fields involved which can reduce the complexity of the file and simplify the program creating or reading the file.

4.1.4 Dimension Maps

Dimension maps are the glue that holds the Swath together. They define the relationship between data fields and geolocation fields by defining, one-by-one, the relationship of each dimension of each geolocation field with the corresponding dimension in each data field. In cases where a data field and a geolocation field share a named dimension, no explicit dimension map is needed. In cases where a data field has more dimensions than the geolocation fields, the "extra" dimensions are left unmapped.

In many cases, the size of a geolocation dimension will be different from the size of the corresponding data dimension. To take care of such occurrences, there are two pieces of information that must be supplied when defining a dimension map: the *offset* and the *increment*. The offset tells how far along a data dimension you must travel to find the first point to have a corresponding entry along the geolocation dimension. The increment tells how many points to travel along the data dimension before the next point is found for which there is a corresponding entry along the geolocation dimension. Figure 4-3 depicts a dimension map.

-

¹ "Co-latitude" may be substituted for "Latitude."




Figure 4-3. A "Normal" Dimension Map

The "data skipping" method described above works quite well if there are fewer regularly spaced geolocation points than data points along a particular pair of mapped dimensions of a Swath. It is conceivable, however, that the reverse is true – that there are more regularly spaced geolocation points than data points. In that event, both the offset and increment should be expressed as negative values to indicate the reversed relationship. The result is shown in Figure 4-4. Note that in the reversed relationship, the offset and increment are applied to the geolocation dimension rather than the data dimension.




Figure 4-4. A "Backwards" Dimension Map

4.1.5 Index

The index was designed specifically for Landsat 7 data products. These products require geolocation information that does not repeat at regular intervals throughout the Swath. The index allows the Swath to be broken into unequal length *scenes* which can be individually geolocated.

For this version of the HDF-EOS library, there is no particular content required for the index. It is quite likely that a later version of the library will impose content requirements on the index in an effort to standardize its use.

4.2 Applicability

The Swath data model is most useful for satellite [or similar] data at a low level of processing. The Swath model is best suited to data at EOS processing levels 1A, 1B, and 2.

4.3 The Swath Data Interface

The SW interface consists of routines for storing, retrieving, and manipulating data in swath data sets.

4.3.1 SW API Routines

All C routine names in the swath data interface have the prefix "SW" and the equivalent FORTRAN routine names are prefixed by "sw." The SW routines are classified into the following categories:

- Access routines initialize and terminate access to the SW interface and swath data sets (including opening and closing files).
- Definition routines allow the user to set key features of a swath data set.
- Basic I/O routines read and write data and metadata to a swath data set.
- *Inquiry* routines return information about data contained in a swath data set.
- Subset routines allow reading of data from a specified geographic region.

The SW function calls are listed in Table 4-1 and are described in detail in the Software Reference Guide that accompanies this document. The page number column in the following table refers to the Software Reference Guide.

Table 4-1. Summary of the Swath Interface (1 of 2)

	Routine Name			Page
Category	С	FORTRAN	Description	Nos.
	SWopen	swopen	Opens or creates HDF file in order to create, read, or write a swath	2-44
	SWcreate	swcreate	Creates a swath within the file	2-6
Access	Swattach	swattach	Attaches to an existing swath within the file	2-2
	SWdetach	swdetach	Detaches from swath interface	2-24
	SWclose	swclose	Closes file	2-4
	SWdefdim	swdefdim	Defines a new dimension within the swath	2-13
	SWdefdimmap	swdefmap	Defines the mapping between the geolocation and data dimensions	2-14
	SWdefidxmap	swdefimap	Defines a non-regular mapping between the geolocation and data dimension	2-18
Definition	SWdefgeofield	swdefgfld	Defines a new geolocation field within the swath	2-16
	SWdefdatafield	swdefdfld	Defines a new data field within the swath	2-11
	SWdefcomp	swdefcomp	Defines a field compression scheme	2-9
	SWwritefield	swwrfld	Writes data to a swath field	2-65
	SWreadfield	swrdfld	Reads data from a swath field.	2-54
Basic I/O	SWwriteattr	swwrattr	Writes/updates attribute in a swath	2-63
	SWreadattr	swrdattr	Reads attribute from a swath	2-53
	SWsetfillvalue	swsetfill	sets fill value for the specified field	2-60
	SWgetfillvalue	swgetfill	Retrieves fill value for the specified field	2-31
	SWinqdims	swinqdims	Retrieves information about dimensions defined in swath	2-37
	SWinqmaps	swinqmaps	Retrieves information about the geolocation relations defined	2-40
	SWinqidxmaps	swinqimaps	Retrieves information about the indexed geolocation/data mappings defined	2-39
	SWinqgeofields	swinqgflds	Retrieves information about the geolocation fields defined	2-38
	SWingdatafields	swingdflds	Retrieves information about the data fields defined	2-35
	SWinqdatatype	swinqdtype	Retrieves information about data type of a field	2-36
	SWingattrs	swingattrs	Retrieves number and names of attributes defined	2-34
Inquiry	SWnentries	swnentries	Returns number of entries and descriptive string buffer size for a specified entity	2-43
	SWdiminfo	swdiminfo	Retrieve size of specified dimension	2-25
	SWmapinfo	swmapinfo	Retrieve offset and increment of specified geolocation mapping	2-42
	SWidxmapinfo	swimapinfo	Retrieve offset and increment of specified geolocation mapping	2-33
	SWattrinfo	swattrinfo	Returns information about swath attributes	2-3
	SWfieldinfo	swfldinfo	Retrieve information about a specific geolocation or data field	2-29
	SWcompinfo	swcompinfo	Retrieve compression information about a field	2-5
	SWinqswath	swinqswath	Retrieves number and names of swaths in file	2-41
	Swregionindex	swregidx	Returns information about the swath region ID	2-56
	SWupdateidxmap	swupimap	Update map index for a specified region	2-61
	SWradefine	swradefine	Defines ragged array	2-48
Ragged	SWraopen	swraopen	Opens ragged array	2-49
Arrays	SWrawrite	swrawrite	Writes data to the ragged array	2-52
-	SWraread	swraread	Reads out data from the ragged array	2-50
	SWraclose	swraclose	Closes the ragged array	2-47

Table 4-1. Summary of the Swath Interface (2 of 2)

	Routine	Name		Page
Category	С	FORTRAN	Description	Nos.
	SWgeomapinfo	swgmapinfo	Retrieves type of dimension mapping when first dimension is geodim	2-32
	SWdefboxregion	swdefboxreg	Define region of interest by latitude/longitude	2-7
	SWregioninfo	swreginfo	Returns information about defined region	2-58
	SWextractregion	swextreg	read a region of interest from a field	2-28
Subset	SWdeftimeperiod	swdeftmeper	Define a time period of interest	2-19
	SWperiodinfo	swperinfo	Retuns information about a defined time period	2-45
	SWextractperiod	swextper	Extract a defined time period	2-27
	SWdefvrtregion	swdefvrtreg	Define a region of interest by vertical field	2-21
	SWdupregion	swdupreg	Duplicate a region or time period	2-26

4.3.2 File Identifiers

As with all HDF-EOS interfaces, file identifiers in the SW interface are 32-bit values, each uniquely identifying one open data file. They are not interchangeable with other file identifiers created with other interfaces.

4.3.3 Swath Identifiers

Before a swath data set is accessed, it is identified by a name which is assigned to it upon its creation. The name is used to obtain a *swath identifier*. After a swath data set has been opened for access, it is uniquely identified by its swath identifier.

4.4 Programming Model

The programming model for accessing a swath data set through the SW interface is as follows:

- 1. Open the file and initialize the SW interface by obtaining a file id from a file name.
- 2. Open OR create a swath data set by obtaining a swath id from a swath name.
- 3. Perform desired operations on the data set.
- 4. Close the swath data set by disposing of the swath id.
- 5. Terminate swath access to the file by disposing of the file id.

To access a single swath data set that already exists in an HDF-EOS file, the calling program must contain the following sequence of C calls:

```
file_id = SWopen(filename, access_mode);
sw_id = SWattach(file_id, swath_name);
<Optional operations>
status = SWdetach(sw_id);
status = SWclose(file_id);
```

To access several files at the same time, a calling program must obtain a separate id for each file to be opened. Similarly, to access more than one swath data set, a calling program must obtain a separate swath id for each data set. For example, to open two data sets stored in two files, a program would execute the following series of C function calls:

```
file_id_1 = SWopen(filename_1, access_mode);
sw_id_1 = SWattach(file_id_1, swath_name_1);
file_id_2 = SWopen(filename_2, access_mode);
sw_id_2 = SWattach(file_id_2, swath_name_2);
<Optional operations>
status = SWdetach(sw_id_1);
status = SWclose(file_id_1);
status = SWclose(file_id_2);
status = SWclose(file_id_2);
```

Because each file and swath data set is assigned its own identifier, the order in which files and data sets are accessed is very flexible. However, it is very important that the calling program individually discard each identifier before terminating. Failure to do so can result in empty or, even worse, invalid files being produced.

5. Grid Data

5.1 Introduction

This section will describe the routines available for storing and retrieving HDF-EOS *Grid Data*. A Grid data set is similar to a swath in that it contains a series of data fields of two or more dimensions. The main difference between a Grid and a Swath is in the character of their geolocation information.

As described in Section 4, swaths carry geolocation information as a series of individually located points (tie points or ground control points). Grids, though, carry their geolocation in a much more compact form. A grid merely contains a set of projection equations (or references to them) along with their relevant parameters. Together, these relatively few pieces of information define the location of all points in the grid. The equations and parameters can then be used to compute the latitude and longitude for any point in the grid.




Figure 5-1. A Data Field in a Mercator-projected Grid

In loose terms, each data field constitutes a map in a given standard projection. Although there may be many independent Grids in a single HDF-EOS file, within each Grid only one projection may be chosen for application to all data fields. Figures 5-1 and 5-2 show how a single data field may look in a Grid using two common projections.

There are three important features of a Grid data set: the data fields, the dimensions, and the projection. Each of these is discussed in detail in the following subsections.




Figure 5-2. A Data Field in an Interrupted Goode's Homolosine-Projected Grid

5.1.1 Data Fields

The data fields are, of course, the most important part of the Grid. Data fields in a Grid data set are rectilinear arrays of two or more dimensions. Most commonly, they are simply two-dimensional rectangular arrays. Generally, each field contains data of similar scientific nature which must share the same data type. The data fields are related to each other by common geolocation. That is, a single set of geolocation information is used for all data fields within one Grid data set.

5.1.2 Dimensions

Dimensions are used to relate data fields to each other and to the geolocation information. To be interpreted properly, each data field must make use of the two predefined dimensions: "XDim" and "YDim". These two dimensions are defined when the grid is created and are used to refer to the X and Y dimensions of the chosen projection (see 5.1.3 below). Although there is no practical limit on the number of dimensions a data field in a Grid data set my have, it is not likely that many fields will need more than three: the predefined dimensions "XDim" and "YDim" and a third dimension for depth or height.

5.1.3 Projections

The projection is really the heart of the Grid. Without the use of a projection, the Grid would not be substantially different from a Swath. The projection provides a convenient way to encode geolocation information as a set of mathematical equations which are capable of transforming Earth coordinates (latitude and longitude) to X-Y coordinates on a sheet of paper.

The choice of a projection to be used for a Grid is a critical decision for a data product designer. There is a large number of projections that have been used throughout history. In fact, some projections date back to ancient Greece. For the purposes of this release of HDF-EOS, however, only six families of projections are supported: Geographic, Interrupted Goode's Homolosine, Polar Stereographic, Universal Transverse Mercator, Space Oblique, and Lambert Azimuthal Equal Area. These projections coincide with those supported by the SDP Toolkit for ECS Release B.

The producer's choice of a projection should be governed by knowledge of the specific properties of each projection and a thorough understanding of the requirements of the data set's users. Two excellent resources for information on projections and their properties are the USGS Professional Papers cited in Section 2.2 "Related Documents."

This release of HDF-EOS assumes that the data producer will use to create the data the General Coordinate Transformation Package (GCTP), a library of projection software available from the U.S. Geological Survey. This manual will not attempt to explain the use of GCTP. Adequate documentation accompanies the GCTP source code. For the purposes of this Grid interface, the data are assumed to have already been projected. The Grid interface allows the data producer to specify the exact GCTP parameters used to perform the projection and will provide for basic subsetting of the data fields by latitude/longitude bounding box.

See section below for further details on the usage of the GCTP package.

5.2 Applicability

The Grid data model is intended for data processed at a high level. It is most applicable to data at EOS processing levels 3 and 4.

5.3 The Grid Data Interface

The GD interface consists of routines for storing, retrieving, and manipulating data in grid data sets.

5.3.1 GD API Routines

All C routine names in the grid data interface have the prefix "GD" and the equivalent FORTRAN routine names are prefixed by "gd." The GD routines are classified into the following categories:

- Access routines initialize and terminate access to the GD interface and grid data sets (including opening and closing files).
- *Definition* routines allow the user to set key features of a grid data set.
- Basic I/O routines read and write data and metadata to a grid data set.
- Inquiry routines return information about data contained in a grid data set.
- Subset routines allow reading of data from a specified geographic region.

The GD function calls are listed in Table 6-1 and are described in detail in the Software Reference Guide that accompanies this document. The page number column in the following table refers to the Software Reference Guide.

Table 5-1. Summary of the Grid Interface (1 of 2)

	Routine	Name		Page
Category	С	FORTRAN	Description	Nos.
	GDopen	gdopen	Creates a new file or opens an existing one	2-108
	GDcreate	gdcreate	Creates a new grid in the file	2-72
Access	GDattach	gdattach	Attaches to a grid	2-68
	GDdetach	gddetach	Detaches from grid interface	2-92
	GDclose	gdclose	Closes file	2-70
	GDdeforigin	gddeforigin	Defines origin of grid	2-81
	GDdefdim	gddefdim	Defines dimensions for a grid	2-78
	GDdefproj	gddefproj	Defines projection of grid	2-83
Definition	GDdefpixreg	gddefpixreg	Defines pixel registration within grid cell	2-82
	GDdeffield	gddeffld	Defines data fields to be stored in a grid	2-79
	GDdefcomp	gddefcomp	Defines a field compression scheme	2-76
	GDwritefield	gdwrfld	Writes data to a grid field.	2-121
	GDreadfield	gdrdfld	Reads data from a grid field	2-114
Basic I/O	GDwriteattr	gdwrattr	Writes/updates attribute in a grid.	2-119
	GDreadattr	gdrdattr	Reads attribute from a grid	2-113
	GDsetfillvalue	gdsetfill	sets fill value for the specified field	2-118
	GDgetfillvalue	gdgetfill	Retrieves fill value for the specified field	2-98
	GDinqdims	gdinqdims	Retrieves information about dimensions defined in grid	2-104
	GDinqfields	gdinqdflds	Retrieves information about the data fields defined in grid	2-105
	GDinqattrs	gdinqattrs	Retrieves number and names of attributes defined	2-102
	GDnentries	gdnentries	Returns number of entries and descriptive string buffer size for a specified entity	2-107
	GDgridinfo	gdgridinfo	Returns dimensions of grid and X-Y coordinates of corners	2-101
Inquiry	GDprojinfo	gdprojinfo	Returns all GCTP projection information	2-112
, ,	GDdiminfo	gddiminfo	Retrieves size of specified dimension.	2-93
	GDcompinfo	gdcompinfo	Retrieve compression information about a field	2-71
	GDfieldinfo	gdfldinfo	Retrieves information about a specific geolocation or data field in the grid	2-96
	GDingdatatype	gdingdtype	Retrieves information about data type of a field	2-103
	GDinggrid	gdinggrid	Retrieves number and names of grids in file	2-106
	GDattrinfo	gdattrinfo	Returns information about grid attributes	2-69
	GDorigininfo	gdorginfo	Return information about grid origin	2-110
	GDpixreginfo	gdpreginfo	Return pixel registration information for given grid	2-111
	GDdefboxregion	gddefboxreg	Define region of interest by latitude/longitude	2-75
	GDregioninfo	gdreginfo	Returns information about a defined region	2-116

Table 5-1. Summary of the Grid Interface (2 of 2)

	Routine Name			Page
Category	С	FORTRAN	Description	Nos.
	GDextractregion	gdextrreg	read a region of interest from a field	2-95
Subset	GDdeftimeperiod	gddeftmeper	Define a time period of interest	2-87
	GDdefvrtregion	gddefvrtreg	Define a region of interest by vertical field	2-89
	GDgetpixels	gdgetpix	get row/columns for lon/lat pairs	2-99
	GDdupregion	gddupreg	Duplicate a region or time period	2-94
Tiling	GDdeftile	gddeftle	Define a tiling scheme	2-85

5.3.2 File Identifiers

As with all HDF-EOS interfaces, file identifiers in the GD interface are 32-bit values, each uniquely identifying one open data file. They are not interchangeable with other file identifiers created with other interfaces.

5.3.3 Grid Identifiers

Before a grid data set is accessed, it is identified by a name which is assigned to it upon its creation. The name is used to obtain a *grid identifier*. After a grid data set has been opened for access, it is uniquely identified by its grid identifier.

5.4 Programming Model

The programming model for accessing a grid data set through the GD interface is as follows:

- 1. Open the file and initialize the GD interface by obtaining a file id from a file name.
- 2. Open OR create a grid data set by obtaining a grid id from a grid name.
- 3. Perform desired operations on the data set.
- 4. Close the grid data set by disposing of the grid id.
- 5. Terminate grid access to the file by disposing of the file id.

To access a single grid data set that already exists in an HDF-EOS file, the calling program must contain the following sequence of C calls:

```
file_id = GDopen(filename, access_mode);
gd_id = GDattach(file_id, grid_name);
<Optional operations>
status = GDdetach(gd_id);
status = GDclose(file id);
```

To access several files at the same time, a calling program must obtain a separate id for each file to be opened. Similarly, to access more than one grid data set, a calling program must obtain a

separate grid id for each data set. For example, to open two data sets stored in two files, a program would execute the following series of C function calls:

```
file_id_1 = GDopen(filename_1, access_mode);
gd_id_1 = GDattach(file_id_1, grid_name_1);
file_id_2 = GDopen(filename_2, access_mode);
gd_id_2 = GDattach(file_id_2, grid_name_2);
<Optional operations>
status = GDdetach(gd_id_1);
status = GDclose(file_id_1);
status = GDclose(file_id_2);
status = GDclose(file_id_2);
```

Because each file and grid data set is assigned its own identifier, the order in which files and data sets are accessed is very flexible. However, it is very important that the calling program individually discard each identifier before terminating. Failure to do so can result in empty or, even worse, invalid files being produced.

5.5 GCTP Usage

The HDF-EOS Grid API uses the U.S. Geological Survey General Cartographic Transformation Package (GCTP) to define and subset grid structures. This section described codes used by the package.

5.5.1 GCTP Projection Codes

The following GCTP projection codes are used in the grid API described in Section 7 below:

```
GCTP_GEO
                  (0)
                        Geographic
                        Universal Transverse Mercator
GCTP_UTM
                  (1)
GCTP LAMCC
                  (4)
                        Lambert Conformal Conic
                        Polar Stereographic
GCTP_PS
                  (6)
GCTP_POLYC
                  (7)
                        Polyconic
GCTP_TM
                  (9)
                        Transverse Mercator
GCTP_LAMAZ
                  (11) Lambert Azimuthal Equal Area
                       Hotine Oblique Mercator
GCTP_HOM
                  (20)
GCTP_SOM
                  (22) Space Oblique Mercator
GCTP_GOOD
                  (24)
                       Interrupted Goode Homolosine
GCTP_ISINUS
                  (99)
                        Intergerized Sinusoidal Projection*
```

Note that other projections supported by GCTP will be adapted for HDF-EOS Version 3 new user requirements are surfaced. For further details on the GCTP projection package, please refer

^{*} The Intergerized Sinusoidal Projection is not part of the original GCTP package. It has been added by ECS. See *Level-3 SeaWiFS Data Products: Spatial and Temporal Binning Algorithms*. Additional references are provided in Section 2.

to Section 6.3.4 and Appendix G of the SDP Toolkit Users Guide for the ECS Project, June 1998, (333-CD-500-001)

5.5.2 UTM Zone Codes

The Universal Transverse Mercator (UTM) Coordinate System uses zone codes instead of specific projection parameters. The table that follows lists UTM zone codes as used by GCTP Projection Transformation Package. C.M. is Central Meridian

Zone	C.M.	Range	Zone	C.M.	Range
01	177W	180W-174W	31	003E	000E-006E
02	171W	174W-168W	32	009E	006E-012E
03	165W	168W-162W	33	015E	012E-018E
04	159W	162W-156W	34	021E	018E-024E
05	153W	156W-150W	35	027E	024E-030E
06	147W	150W-144W	36	033E	030E-036E
07	141W	144W-138W	37	039E	036E-042E
08	135W	138W-132W	38	045E	042E-048E
09	129W	132W-126W	39	051E	048E-054E
10	123W	126W-120W	40	057E	054E-060E
11	117W	120W-114W	41	063E	060E-066E
12	111W	114W-108W	42	069E	066E-072E
13	105W	108W-102W	43	075E	072E-078E
14	099W	102W-096W	44	081E	078E-084E
15	093W	096W-090W	45	087E	084E-090E
16	087W	090W-084W	46	093E	090E-096E
17	081W	084W-078W	47	099E	096E-102E
18	075W	078W-072W	48	105E	102E-108E
19	069W	072W-066W	49	111E	108E-114E
20	063W	066W-060W	50	117E	114E-120E
21	057W	060W-054W	51	123E	120E-126E
22	051W	054W-048W	52	129E	126E-132E
23	045W	048W-042W	53	135E	132E-138E
24	039W	042W-036W	54	141E	138E-144E
25	033W	036W-030W	55	147E	144E-150E

26	027W	030W-024W	56	153E	150E-156E
27	021W	024W-018W	57	159E	156E-162E
28	015W	018W-012W	58	165E	162E-168E
29	009W	012W-006W	59	171E	168E-174E
30	003W	006W-000E	60	177E	174E-180W

5.5.3 GCTP Spheroid Codes

Clarke 1866 (default)	(0)
Clarke 1880	(1)
Bessel	(2)
International 1967	(3)
International 1909	(4)
WGS 72	(5)
Everest	(6)
WGS 66	(7)
GRS 1980	(8)
Airy	(9)
Modified Airy	(10)
Modified Everest	(11)
WGS 84	(12)
Southeast Asia	(13)
Austrailian National (14)	
Krassovsky (15)	
Hough (16)	
Mercury 1960	(17)
Modified Mercury 1968	(18)
Sphere of Radius 6370997m	(19)

5-8

5.5.4 Projection Parameters

Table 5-2. Projection Transformation Package Projection Parameters

	Array Element							
Code & Projection Id	1	2	3	4	5	6	7	8
0 Geographic								
1 U T M	Lon/Z	Lat/Z						
4 Lambert Conformal C	SMajor	SMinor	STDPR1	STDPR2	CentMer	OriginLat	FE	FN
6 Polar Stereographic	SMajor	SMinor			LongPol	TrueScale	FE	FN
7 Polyconic	SMajor	SMinor			CentMer	OriginLat	FE	FN
9 Transverse Mercator	SMajor	SMinor	Factor		CentMer	OriginLat	FE	FN
11 Lambert Azimuthal	Sphere				CentLon	CenterLat	FE	FN
20 Hotin Oblique Merc A	SMajor	SMinor	Factor			OriginLat	FE	FN
20 Hotin Oblique Merc B	SMajor	SMinor	Factor	AziAng	AzmthPt	OriginLat	FE	FN
22 Space Oblique Merc A	SMajor	SMinor		IncAng	AscLong		FE	FN
22 Space Oblique Merc B	SMajor	SMinor	Satnum	Path			FE	FN
24 Interrupted Goode	Sphere							
99 Integerized Sinusoidal	Sphere				CentMer		FE	FN

Table 5-3. Projection Transformation Package Projection Parameters Elements

	Array Element							
Code & Projection Id	9	10	11	12	13			
0 Geographic								
1 U T M								
4 Lambert Conformal C								
6 Polar Stereographic								
7 Polyconic								
9 Transverse Mercator								
11 Lambert Azimuthal								
20 Hotin Oblique Merc A	Long1	Lat1	Long2	Lat2	zero			
20 Hotin Oblique Merc B					one			
22 Space Oblique Merc A	PSRev	Srat	PFlag		zero			
22 Space Oblique Merc B					one			
24 Interrupted Goode								
99 Integerized Sinusoidal	NZone		RFlag					

Where,

Lon/Z Longitude of any point in the UTM zone or zero. If zero, a zone code must be

specified.

Lat/Z Latitude of any point in the UTM zone or zero. If zero, a zone code must be

specified.

Smajor Semi-major axis of ellipsoid. If zero, Clarke 1866 in meters is assumed.

Sminor Eccentricity squared of the ellipsoid if less than zero, if zero, a spherical form is

assumed, or if greater than zero, the semi-minor axis of ellipsoid.

Sphere Radius of reference sphere. If zero, 6370997 meters is used.

STDPR1 Latitude of the first standard parallel

STDPR2 Latitude of the second standard parallel

CentMer Longitude of the central meridian

OriginLat Latitude of the projection origin

FE False easting in the same units as the semi-major axis

FN False northing in the same units as the semi-major axis

TrueScale Latitude of true scale

LongPol Longitude down below pole of map

Factor Scale factor at central meridian (Transverse Mercator) or center of projection

(Hotine Oblique Mercator)

CentLon Longitude of center of projection

CenterLat Latitude of center of projection

Long1 Longitude of first point on center line (Hotine Oblique Mercator, format A)

Long2 Longitude of second point on center line (Hotine Oblique Mercator, frmt A)

Latitude of first point on center line (Hotine Oblique Mercator, format A)

Latitude of second point on center line (Hotine Oblique Mercator, format A)

AziAng Azimuth angle east of north of center line (Hotine Oblique Mercator, frmt B)

AzmthPt Longitude of point on central meridian where azimuth occurs (Hotine Oblique

Mercator, format B)

IncAng Inclination of orbit at ascending node, counter-clockwise from equator (SOM,

format A)

AscLong Longitude of ascending orbit at equator (SOM, format A)

PSRev Period of satellite revolution in minutes (SOM, format A)

SRat Satellite ratio to specify the start and end point of x,y values on earth surface (SOM,

format A -- for Landsat use 0.5201613)

PFlag End of path flag for Landsat: 0 = start of path, 1 = end of path (SOM, frmt A)

Satnum Landsat Satellite Number (SOM, format B)

Path Landsat Path Number (Use WRS-1 for Landsat 1, 2 and 3 and WRS-2 for Landsat 4

and 5.) (SOM, format B)

Nzone Number of equally spaced latitudinal zones (rows); must be two or larger and even

Rflag Right justify columns flag is used to indicate what to do in zones with an odd

number of columns. If it has a value of 0 or 1, it indicates the extra column is on the right (zero) left (one) of the projection Y-axis. If the flag is set to 2 (two), the number of columns are calculated so there are always an even number of columns

in each zone.

Notes:

• Array elements 14 and 15 are set to zero.

• All array elements with blank fields are set to zero.

All angles (latitudes, longitudes, azimuths, etc.) are entered in packed degrees/ minutes/ seconds (DDDMMMSSS.SS) format.

The following notes apply to the Space Oblique Mercator A projection:

- A portion of Landsat rows 1 and 2 may also be seen as parts of rows 246 or 247. To place these locations at rows 246 or 247, set the end of path flag (parameter 11) to 1--end of path. This flag defaults to zero.
- When Landsat-1,2,3 orbits are being used, use the following values for the specified parameters:
 - Parameter 4 099005031.2
 - Parameter 5
 128.87 degrees (360/251 * path number) in packed DMS format
 - Parameter 9 103.2669323
 - Parameter 10 0.5201613
- When Landsat-4,5 orbits are being used, use the following values for the specified parameters:
 - Parameter 4 098012000.0
 - Parameter 5 129.30 degrees (360/233 * path number) in packed DMS format
 - Parameter 9 98.884119
 - Parameter 10 0.5201613

6. Examples of HDF-EOS Library Usage

This Section contains code examples of usage of the HDF-EOS Library specified in Volume 2 of this document. These examples assume that the user is not using the SDP Toolkit and is writing applications for use outside of ECS. Examples of SDP Toolkit usage in conjunction with HDF-EOS is presented in Section 7.

Note: The examples in this document are code fragments, designed to show users how to create HDF-EOS data structures. Some of the examples in this version have not yet undergone thorough inspections and checks for ECS software standard compliance.

6.1 Swath Examples

This section contains several examples of the use of the Swath interface from both C and FORTRAN programs. First, there are simple examples in C and FORTRAN which demonstrate the use of most of the functions in the Swath interface. The section concludes with a real world example from the ECS "V0 Data Migration" effort, written in C.

6.1.1 Creating a Simple Swath

The following C and FORTRAN programs each create, define, and write a simple Swath data set to an HDF-EOS file using the HDF-EOS Swath interface.

6.1.1.1 A C Example of a Simple Swath Creation

The following C source code is part of a test driver that demonstrates the functioning of the Swath interface routines.

Note: This is a test example; it is presented for the purpose of providing a guide for users of HDF-EOS.

```
hssize_t start[2] = {10, 10};
hssize_t tstart[2] = {0, 0};
hssize t geostart[2] = \{0, 0\};
hsize_t stride[2] = {1, 1};
hsize_t edge[2] = {90, 30};
hsize_t tedge[2] = {100, 40};
hsize t geostride[2] = \{1,1\};
hsize t geocount[2] = \{50,40\};
float32 temp[100][40];
float32 cond[100][40];
float32 cnt = -799.;
float lat[50][40];
float latcnt = 39.8;
float lon[50][40];
float loncnt = 78.0;
/* ----- */
/* and "Conduction" data fields
/* ----- */
while(index1 < 100) {
  while (index2 < 40) {
     temp[index1][index2] = cnt;
     cond[index1][index2] = cnt + .1;
     index2++;
     cnt = cnt + .1;
   index1++;
  index2 = 0;
/* ----- */
/* populate data arrays for the "Latitude" and */
/* "Longitude" geolocation data fields */
/* ----- */
index1 = 0;
index2 = 0;
while (index1 < 50) {
  while (index2 < 40) {
     lat[index1][index2] = latcnt;
     lon[index1][index2] = loncnt;
     loncnt = loncnt - .1;
     index2++;
   latcnt = latcnt - .1;
   loncnt = 78.0;
  index1++;
  index2 = 0;
}
```

```
/* Open HDF-EOS file "Swath.h5" 5(if the named */
  /* file does not exist, it will be automatically
  /* created with the read/write access mode */
  /* -----*/
  swfid = SWopen("Swath.h5", H5F ACC TRUNC);
  /* Create swath "Simple" within HDF-EOS file
  /* "Swath.h5"
  /* ----- */
  SWid simple = SWcreate(swfid, "Simple");
  /* Define dimensions
  /* ----- */
 status = SWdefdim(SWid_simple, "DataTrack", 100);
status = SWdefdim(SWid_simple, "DataXtrack", 40);
status = SWdefdim(SWid_simple, "GeoTrack", 50);
  status = SWdefdim(SWid simple, "GeoXtrack", 40);
  status = SWdefdatafield(SWid simple, "Temperature",
"DataTrack,DataXtrack",
        "DataTrack, DataXtrack", H5T NATIVE FLOAT, HDFE AUTOMERGE);
  status = SWdefdatafield(SWid simple, "Conduction", "DataTrack, DataXtrack",
         "DataTrack, DataXtrack", H5T NATIVE FLOAT, HDFE NOMERGE);
  /* Define geolocation fields
  /* ----- */
  status = SWdefgeofield(SWid simple, "Latitude", "GeoTrack, GeoXtrack",
       H5T NATIVE FLOAT, HDFE AUTOMERGE);
  status = SWdefgeofield(SWid_simple, "Longitude", "GeoTrack, GeoXtrack",
        "GeoTrack, GeoXtrack", H5T NATIVE FLOAT, HDFE AUTOMERGE);
  /* Define mapping between different dimensions */
  /* ----- */
  status = SWdefdimmap(SWid_simple, "GeoTrack", "DataTrack", 0, 2);
status = SWdefdimmap(SWid_simple, "GeoXtrack", "DataXtrack", 0, 1);
  /* ----- */
  /* Detach from the swath
  /* -----
  status = SWdetach(SWid_simple);
  /* ----- */
  /* ----- */
  SWid simple = SWattach(swfid, "Simple");
  /* ----- */
  /* Write the temperature data to the swath
```

```
/* ----- */
 status = SWwritefield(SWid simple, "Temperature", tstart, stride, tedge,
temp);
 /* ----- */
 /* ----- */
 status = SWwritefield(SWid simple, "Conduction", start, stride, edge,
cond);
 /* ----- */
 /* ----- */
 status = SWwritefield(SWid simple, "Latitude", geostart, geostride,
geocount, lat);
 /* ----- */
 /* ----- */
 status = SWwritefield(SWid simple, "Longitude", geostart, geostride,
geocount, lon);
 /* ----- */
 /* Close the HDF-EOS file "Swath.h5"
 /* ----- */
 status = SWclose(swfid);
```

6.1.1.2 FORTRAN Example of a Simple Swath Creation

```
Simple driver to create and write data
to the HDF-EOS swath file
 implicit none
integer status
integer i
 integer index1
integer index2
 integer swfid
            SWid simple
 integer
 integer*4 start(2)
 integer*4 tstart(2)
 integer*4 geostart(2)
 integer*4 stride(2)
 integer*4 tstride(2)
 integer*4 edge(2)
 integer*4 tedge(2)
 integer*4 geostride(2)
 integer*4 geocount(2)
 real*8 TimeData(5)
```

```
temp(100,40)
cond(100,40)
cnt
lat(50,40)
latcnt
lon(50,40)
loncnt
      real*4
      real*4
      real*4
      real*4
      real*4
      real*4
                  loncnt
                swclose, swopen, swcreate, swdefdim
      integer
                swdefdfld, swdefgfld, swdefmap, swattach, swdetach
      integer
      integer
                  swwrfld
      integer H5F ACC TRUNC
      parameter (\overline{H5F} \ \overline{ACC} \ TRUNC = 2)
      integer HDFE AUTOMERGE
      parameter ( HDFE AUTOMERGE = 1)
      integer HDFE NOMERGE
      parameter (\overline{HDFE} NOMERGE = 0)
      integer H5T_NATIVE_INT
      parameter (H5T NATIVE INT = 0)
      integer H5T NATIVE FLOAT
      parameter ( H5T NATIVE FLOAT = 1)
      integer H5T NATIVE DOUBLE
     parameter ( H5T NATIVE DOUBLE = 2)
      status
                 = -1
      swfid = -1
      SWid simple = -1
      start(1) = 10

start(2) = 10
     tstart(1) = 0

tstart(2) = 0
      geostart(1) = 0
      geostart(2) = 0
      stride(1) = 1
      stride(2) = 1
                 = 90
      edge(1)
                 = 30
      edge(2)
               = 100
      tedge(1)
      tedge(2)
                 = 40
      geostride(1) = 1
      geostride(2) = 1
      geocount(1) = 50
      geocount(2) = 40
      = -799.
                 = 39.8
      latcnt
      loncnt
                 = 78.0
  populate data arrays for the "Temperature"
   and "Conduction" data fields
С
   _____
С
      do 20 index1 =1, 100
         do 10 index2 =1, 40
            temp(index1, index2) = cnt
            cond(index1, index2) = cnt + .1
            cnt = cnt + .1
```

real*4

```
10 continue
20 continue
  populate data arrays for the "Latitude" and
С
      "Longitude" geolocation data fields
C
     do 40 index1 =1, 50
        do 30 index2 =1, 40
           lat(index1,index2) = latcnt
           lon(index1, index2) = loncnt
           loncnt = loncnt - .1
30
        continue
        latcnt = latcnt - .1
        loncnt = 78.0
     continue
    Open HDF-EOS file "Swath.h5" (if the named
С
   file does not exist, it will be automatically
    created with the read/write access mode
     swfid = SWopen("Swath.h5", H5F_ACC_TRUNC)
  Create swath "Simple" within HDF-EOS file
   "Swath.h5"
С
  -----
     SWid simple = SWcreate(swfid, "Simple")
  _____
 Define dimensions
     status = SWdefdim(SWid simple, "DataTrack", 100)
     status = SWdefdim(SWid_simple, "DataXtrack", 40)
     status = SWdefdim(SWid simple, "GeoTrack", 50)
     status = SWdefdim(SWid simple, "GeoXtrack", 40)
  Define data fields
     status = SWdefdfld(SWid simple, "Temperature",
          "DataTrack, DataXtrack",
          "", H5T NATIVE FLOAT, HDFE_AUTOMERGE)
     status = SWdefdfld(SWid simple, "Conduction",
          "DataTrack, DataXtrack",
          "", H5T NATIVE_FLOAT, HDFE_NOMERGE)
  Define geolocation fields
     status = SWdefgfld(SWid_simple, "Latitude",
          "GeoTrack, GeoXtrack", "", H5T_NATIVE_FLOAT, HDFE_AUTOMERGE)
     status = SWdefgfld(SWid_simple, "Longitude",
    > "GeoTrack, GeoXtrack", "", H5T NATIVE FLOAT
```

```
> ,HDFE_AUTOMERGE)
    Status = SWdefgfld(SWid simple, "Time", "GeoTrack", "",
    > H5T NATIVE DOUBLE, HDFE AUTOMERGE)
    .______
 Define mapping between different dimensions
    status = SWdefmap(SWid_simple, "GeoTrack", "DataTrack", 0, 2)
    status = SWdefmap(SWid simple, "GeoXtrack", "DataXtrack", 0, 1)
  _____
 Detach from the swath
  ______
    status = SWdetach(SWid simple)
С
 Re-attach to the sawth
  ______
    SWid simple = SWattach(swfid, "Simple")
c Write the temperature data to the swath
    status = SWwrfld(SWid simple, "Temperature", tstart, stride,
   > tedge, temp)
 Write the conduction data to the swath
    status = SWwrfld(SWid simple, "Conduction", start, stride,
   > edge, cond)
 Write the Latitude data to the swath
  ______
    status = SWwrfld(SWid simple, "Latitude", geostart, geostride
   > , geocount, lat)
 Write the Longitude data to the swath
  _____
    status = SWwrfld(SWid simple, "Longitude", geostart,
       geostride, geocount, lon)
c----- \mbox{Writing Time} in a swath -----
    do 120 i=1,5
      TimeData(i) = 5.e7 + 5.e6 *i
120 continue
    tstart(1) = 0
    tstride(1) = 1

tedge(1) = 5
    Status = SWwrfld(SWid_simple, "Time", tstart, tstride, tedge,
        TimeData)
```

6.1.2 Performing Subsetting for a Swath

The following C and FORTRAN programs each demonstrate how to perform subsetting for a Swath object in an HDF-EOS file using the HDF-EOS Swath interface.

6.1.2.1 The C Examples of a Subsetting for a Swath

```
Example 1:
/* -----
/* Simple driver to define time period for a swath, and then extract
*/ /* the entries of a specified data field within the defined time period.
*/ /* NOTE: Before running this driver make sure that the
file, Swathc Test.h5, */
          produced by a test driver testswath_he3.c exists.
*/
/* -----
#include "HdfEosDef.h"
main(int argc, char *argv[])
  herr_t status;
  hid_t swfidc_test;
hid_t SWid_co;
  int32_t i, j, k;
  int32_t periodID;
  int32_t rank, size;
  hsize t dims[8];
  H5T class t
            *numtype = (H5T_class_t *)NULL;
  float64 *timebuf;
  float64 starttime, stoptime;
```

```
/* Open HDF-EOS swath file and attach to the named swath */
   swfidc test = SWopen("Swathc Test.h5", H5F ACC RDONLY);
  printf("\t\tSwath file ID returned by SWopen %d\n", swfidc test);
  SWid co = SWattach(swfidc test, "Swathco");
  printf("\t\tSwath ID returned by SWattach on swath Swathco %d\n", SWid co);
/* ----- */
/* Define time period
  starttime = 46353450.0;
  stoptime = 46500000.0;
  periodID = SWdeftimeperiod(SWid co,starttime,stoptime,HDFE MIDPOINT);
  printf("\t\tPeriod id returned by SWdeftimeperiod %d\n",periodID);
     Retrieve basic information about data fields "BandC" */
      and "Time"
  numtype = (H5T class t *)calloc(1, sizeof(H5T class t));
   status = SWperiodinfo(SWid co,periodID, "BandC", numtype, &rank, dims, &size);
           printf("\t\tStatus returned by SWperiodinfo %d\n", status);
           printf("\t\tNumber type of region %d, Rank of region
%d\n", *numtype, rank);
           printf("\t\tDimensions of region %lu %lu \n", (unsigned
long)dims[0], (unsigned long)dims[1]);
           printf("\t\tSize of region in bytes %d\n", size);
  status = SWperiodinfo(SWid co,periodID, "Time", numtype, &rank, dims, &size);
  printf("\t\tStatus returned by SWperiodinfo %d\n", status);
           printf("\t\tNumber type of region %d, Rank of region
%d\n",*numtype,rank);
           printf("\t\tDimensions of region %lu %lu \n", (unsigned
long)dims[0], (unsigned long)dims[1]);
           printf("\t\tSize of region in bytes %d\n",size);
  free (numtype);
  timebuf = (float64 *)malloc(size);
   status = SWextractperiod(SWid co,periodID, "Time", HDFE INTERNAL, timebuf);
  printf("\t\tStatus returned by SWextractperiod %d\n", status);
     for(i = 0; i < 10; i++)
        for(j = 0; j < 5; j++)
           printf("\t\t %d %d %f\n", i, j, timebuf[k]);
           k++;
   free(timebuf);
```

```
status = SWdetach(SWid co);
  printf("\t\tStatus returned by SWdetach %d\n", status);
  status=SWclose(swfidc test);
}
Example 2 :
/* ----- */
/* Simple driver demonstrating how to perform subsetting along the "Track" */
/* dimension and along any other dimension defined in a specified swath. */
/* NOTE:
                                                            * /
/* make sure that the HDF-EOS file Swathc Test.h5 produced by the test
                                                           * /
/* driver testswath he3.c exists.
/* ----- */
#include "HdfEosDef.h"
main()
  herr t status;
  H5T_class_t *numtype = (H5T class t *)NULL;
  float32 *datbuf;
float64 *timebuf;
  float64 corlon[2], corlat[2], range[2];
/* -----
* /
*/
/* Open swath file "Swathc_Test.h5" and attach to the named swath
objects.*/
/* -----
  swfidc test = SWopen("Swathc Test.h5", H5F ACC RDONLY);
  printf("\t\tSwath file ID returned by SWopen \(\frac{1}{8}d\n\)", swfidc test);
  SWid oned = SWattach(swfidc test, "OnedGeo");
  printf("\t\tSwath ID returned by SWattach on swath \"OnedGeo\"
%d\n",SWid oned);
  SWid simple = SWattach(swfidc test, "Simple");
  printf("\t\tSwath ID returned by SWattach on swath \"Simple\"
%d\n",SWid simple);
  SWid index = SWattach(swfidc test, "Index");
  printf("\t\tSwath ID returned by SWattach on swath \"Index\"
%d\n",SWid index);
```

```
/*
          1.1 Perform subsetting on the named field
  range[0] = 46353450.0;
   range[1] = 46500000.0;
   regionID = SWdefvrtregion(SWid oned, HDFE NOPREVSUB, "Time", range);
  printf("\t\tRegion id returned by SWdefvrtregion %d\n",regionID);
* /
/*
     1.2 Retrieve information about the subsetted region
*/
                  for the named data field
* /
  numtype = (H5T class t *)calloc(1, sizeof(H5T class t));
   status = SWregioninfo(SWid oned,
regionID, "Time", numtype, &rank, dims, &size);
  printf("\t\tStatus returned by SWregioninfo %d\n", status);
  printf("\t\tNumber type of field %d\n", *numtype);
  printf("\t\tRank of field %d\n",rank);
  printf("\t\tDimension of subsetted region: %lu \n", (unsigned
long)dims[0]);
  printf("\t\tSize in bytes of region %d\n", size);
   free(numtype);
*/
/*
          1.3 Read data into the data buffer from the subsetted region
* /
   timebuf = (float64 *)malloc(size);
   status = SWextractregion(SWid oned, regionID,
"Time", HDFE INTERNAL, timebuf);
  printf("\t\tStatus returned by SWextractregion %d\n", status);
        for (k = 0; k < 5; k++)
            printf("\t\t%d %f \n", k, timebuf[k]);
   free(timebuf);
   status = SWdetach(SWid oned);
  printf("\t\tStatus returned by SWdetach %d\n", status);
```

```
/*
           2.1 Define a longitude-latitude box region for the named swath
   corlon[0] = 75.5;
   corlat[0] = 35.5;
   corlon[1] = 77.5;
   corlat[1] = 36.5;
   regionID = SWdefboxregion(SWid simple,corlon,corlat,HDFE MIDPOINT);
  printf("\t\tSwath region ID returned by SWdefboxregion %d\n", regionID);
* /
/*
        2.2 Retrieve information about the subsetted region
*/
                  for the named data field
* /
   numtype = (H5T class t *)calloc(1, sizeof(H5T class t));
   status = SWregioninfo(SWid simple,
regionID, "Temperature", numtype, &rank, dims, &size);
  printf("\t\tStatus returned by SWregioninfo %d\n", status);
  printf("\t\tNumber type of field %d\n", *numtype);
  printf("\t\tRank of field %d\n",rank);
   printf("\t\tDimensions of subsetted region: %lu , %lu \n", (unsigned
long)dims[0], (unsigned long)dims[1]);
  printf("\t\tSize in bytes of region %d\n", size);
   free(numtype);
*/
       2.3 Read data into the data buffer from the subsetted region
* /
   datbuf = (float32 *)malloc(size);
   status = SWextractregion(SWid simple, regionID,
"Temperature", HDFE INTERNAL, datbuf);
   printf("\t\tStatus returned by SWextractregion %d\n", status);
     k = 0;
      for( i = 0; i < 10; i++)
         for (j = 0; j < 5; j++)
            printf("\t\t\d\ %d\ %f\n", i, j, datbuf[k]);
            k++;
      }
   free (datbuf);
```

```
/*
      2.4 Retrieve information about the subsetted region
/*
                  for the named data field
* /
  numtype = (H5T_class_t *)calloc(1, sizeof(H5T_class_t));
  status = SWregioninfo(SWid simple, regionID, "Latitude", numtype, &rank,
dims, &size);
  printf("\t\tStatus returned by SWregioninfo %d\n", status);
  printf("\t\tNumber type of field %d\n", *numtype);
  printf("\t\tRank of field %d\n", rank);
  printf("\t\tDimensions of subsetted region: %lu , %lu \n", (unsigned
long)dims[0], (unsigned long)dims[1]);
  printf("\t\tSize in bytes of region %d\n", size);
  free (numtype);
       2.5 Read data into the data buffer from the subsetted region
*/
     _____
  datbuf = (float32 *)malloc(size);
   status = SWextractregion(SWid simple, regionID, "Latitude", HDFE INTERNAL,
  printf("\t\tStatus returned by SWextractregion %d\n", status);
     for(i = 0; i < 10; i++)
        for(j = 0; j < 5; j++)
           printf("\t\t %d %d %f\n", i, j, datbuf[k]);
           k++;
  free(datbuf);
   status = SWdetach(SWid simple);
  printf("\t\tValue returned by SWdetach %d\n", status);
       3.1 Define a longitude-latitude box region for the named swath
  corlat[0] = 37.0;
  corlat[1] = 38.5;
  corlon[0] = 76.0;
  corlon[1] = 77.5;
```

```
regionID = SWdefboxregion(SWid index, corlon, corlat, HDFE MIDPOINT);
  printf("\t\tRegion ID returned by SWdefboxregion %d\n", regionID);
      ._____
*/
      3.2 Retrieve information about the subsetted region
* /
/*
                for the named data field
  numtype = (H5T class t *)calloc(1, sizeof(H5T class t));
  status = SWregioninfo(SWid index, regionID, "Fakedata", numtype, &rank,
dims, &size);
  printf("\t\tStatus returned by SWregioninfo %d\n", status);
  printf("\t\tNumber type of field %d\n", *numtype);
  printf("\t\tRank of field %d\n", rank);
  printf("\t\tDimensions of subsetted region: %lu , %lu\n", (unsigned
long)dims[0], (unsigned long)dims[1]);
  printf("\t\tSize in bytes of region %d\n", size);
/* -----
    3.3 Read data into the data buffer from the subsetted region
/* -----
  datbuf = (float32 *)malloc(size);
  status = SWextractregion(SWid index, regionID, "Fakedata", HDFE INTERNAL,
datbuf);
  printf("\t\tStatus returned by SWextractregion %d\n", status);
     k = 0;
     for(i = 0; i < 10; i++)
       printf("\t\t%d %f\n", i, datbuf[k]);
       k++;
     }
  free (datbuf);
  free (numtype);
  status = SWdetach(SWid index);
  status = SWclose(swfidc test);
```

6.1.2.2 The FORTRAN Examples of a Subsetting for a Swath

```
Example 1 :

c ------
c Simple driver to define time period for a swath, and then extract all the
c entries of a specified data field within the defined time period.
```

```
NOTE: Before running this driver make sure that the file, Swathc_Test.h5,
   produced by a test driver testswath he3.c exists.
С
C
     implicit none
integer status
     integer swfidc_test
               SWid co
     integer
     integer*4 k
     integer*4 periodID
     integer*4 rank, size
     integer*4 dims(8)
     integer
               numtype(1)
     starttime, stoptime
     integer swclose, swdetach, swextper, swperinfo
integer swopen, swattach, SWdeftmeper
integer H5F_ACC_RDONLY
     parameter (H\overline{5}F A\overline{C}C RDONLY = 0)
     integer*4 HDFE MIDPOINT
     parameter ( HDFE MIDPOINT = 0)
     integer*4 HDFE INTERNAL
     parameter ( HDFE INTERNAL = 0)
   Open HDF-EOS swath file and attach to the named swath
С
     swfidc test = SWopen("Swath.h5", H5F ACC RDONLY)
     print \overline{*},' Swath file ID returned by SWopen = ', swfidc test
     SWid co = SWattach(swfidc test, "Simple")
     print *,' Swath ID returned by SWattach on swath Swathco = '
      ,SWid co
      Define time period
C
 ______
     starttime = 5.5e7
     stoptime = 6.5e7
     periodID = SWdeftmeper(SWid_co,starttime,stoptime,HDFE_MIDPOINT)
               Period id returned by SWdeftimeperiod = ',periodID
     print *,'
            _____
     Retrieve basic information about data fields "BandC"
С
           and "Time"
С
     status = SWperinfo(SWid co,periodID, "Time", numtype, rank, dims
```

```
> ,size)
              Status returned by SWperiodinfo = ', status Number type of region = ', numtype,
     print *,'
     print *,'
    > 'Rank of region = ', rank

print *,' Dimensions of region = ', dims(1),' ', dims(2)

print *,' Size of region in bytes = ', size
     status = SWperinfo(SWid co,periodID, "Time", numtype, rank
              ,dims,size)
     print *,'
                Status returned by SWperiodinfo = ',status
     print *,'
                   Number type of region = ', numtype,
             Rank of region = ',rank
    > '
     print *
                 Dimensions of region = ', dims(1), ' ', dims(2)
     print *,'
                   Size of region in bytes = ',size
     status = SWextper(SWid co,periodID, "Time", HDFE INTERNAL
    > ,timebuf)
     print *,'
                   Status returned by SWextractperiod = ', status
        do 10 k = 1, dims(1)
          print *,' k=', k, ' timebuf(', k,') = ', timebuf(k)
10
        continue
     status = SWdetach(SWid co)
     print *,' Status returned by SWdetach = ',status
     status=SWclose(swfidc test)
     stop
     end
Example 2 :
c ------
c Simple driver demonstrating how to perform subsetting along the "Track"
c dimension and along any other dimension defined within a specified swath.
c NOTE: make sure that the HDF-EOS file Swathc Test.h5 produced by the test
c driver testswath he3.c exists.
c -----
     implicit none
     integer
               status
     integer
               swfidc test, SWid simple, SWid oned, SWid index
     integer*4 rank, size, regionID
     integer i,j,k
     integer*4 dims(8)
     integer numtype
     real*4
               datbuf(48000)
            timebuf (48000)
     real*8
     real*8 corlon(2), corlat(2), range(2)
     integer swopen, swattach, swdefvrtreg, swreginfo, swextreg
```

```
integer swdetach, swclose
     integer*4 swdefboxreg
     integer H5F_ACC_RDONLY
parameter ( H5F_ACC_RDONLY = 0)
integer*4 HDFE_MIDPOINT
parameter ( HDFE_MIDPOINT = 0)
     integer*4 HDFE INTERNAL
     parameter ( HD\overline{F}E INTERNAL = 0)
     integer HDFE NOPREVSUB
     parameter ( HDFE_NOPREVSUB = -1)
c ------
 Open swath file "Swathc_Test.h5" and attach to the named swath objects.
c -----
     swfidc test = SWopen("Swathc Test.h5", H5F ACC RDONLY)
     print *,' Swath file ID returned by SWopen = ',swfidc_test
     SWid oned = SWattach(swfidc test, "OnedGeo")
     print *,' Swath ID returned by SWattach on swath "OnedGeo" = '
    > ,SWid oned
     SWid simple = SWattach(swfidc test, "Simple")
     print *,' Swath ID returned by SWattach on swath "Simple" = '
    > ,SWid simple
     SWid index = SWattach(swfidc test, "Index")
     print *,' Swath ID returned by SWattach on swath "Index" = '
    > ,SWid index
c -----
        1.1 Perform subsetting on the named field
     range(1) = 46353450.0
     range(2) = 46500000.0
     regionID = SWdefvrtreg(SWid oned, HDFE NOPREVSUB, "Time", range)
     print *,' Region id returned by SWdefvrtregion = ',regionID
c 1.2 Retrieve information about the subsetted region
               for the named data field
C -----
     status = SWreginfo(SWid oned, regionID, "Time", numtype, rank, dims
        ,size)
     print *,' Status returned by SWregioninfo = ', status
print *,' Number type of field = ', numtype
print *,' Rank of field = ',rank
print *,' Dimension of subsetted region: ', dims(1)
print *,' Size in bytes of region = ',size
C -----
```

```
c 1.3 Read data into the data buffer from the subsetted region
     status = SWextreg(SWid oned, regionID, "Time", HDFE INTERNAL
     print *,' Status returned by SWextractregion = ', status do 10 k = 1, 5
       print *,' k=', k,' timebuf(', k,') = ', timebuf(k)
10
     continue
     status = SWdetach(SWid oned)
     print *,' Status returned by SWdetach = ',status
C -----
        2.1 Define a longitude-latitude box region for the named swath
     corlon(1) = 75.5
     corlat(1) = 35.5
     corlon(2) = 77.5
     corlat(2) = 36.5
     regionID = SWdefboxreg(SWid simple, corlon, corlat, HDFE MIDPOINT)
     print *,' Swath region ID returned by SWdefboxregion = ',
        regionID
c 2.2 Retrieve information about the subsetted region
         for the named data field
     status = SWreginfo(SWid simple, regionID, "Temperature", numtype
    > ,rank,dims,size)
     print *,'
               Status returned by SWregioninfo = ', status
     print *,'
               Number type of field = ', numtype
     print *,' Rank of field = ',rank
print *,' Dimensions of subsetted region: ', dims(1), dims(2)
print *,' Size in bytes of region = ',size
c ------
    2.3 Read data into the data buffer from the subsetted region
     status = SWextreg(SWid simple, regionID, "Temperature"
    > ,HDFE_INTERNAL,datbuf)
     print *,' Status returned by SWextractregion = ', status
     k = 1
     do 30 i = 1,10
        do 20 j = 1, 5 print *,' i=', i,' j=', j, ' datbuf(',k,')=',datbuf(k)
           k=k+1
20
        continue
30 continue
```

```
2.4 Retrieve information about the subsetted region
        for the named data field
    status = SWreginfo(SWid simple, regionID, "Latitude", numtype, rank
    > , dims, size)
    print *,'
             Status returned by SWregioninfo = ', status
    print *,'
              Number type of field = ', numtype
    print *,' Rank of field = ', rank
print *,' Dimensions of subsetted region: ',dims(1),dims(2)
print *,' Size in bytes of region = ', size
     2.5 Read data into the data buffer from the subsetted region
c ------
    status = SWextreg(SWid simple, regionID, "Latitude", HDFE INTERNAL
    > , datbuf)
    print *,' Status returned by SWextractregion = ', status
    k = 1
     do 50 i = 1,10
       do 40 j = 1, 5
          print *,' i=', i,' j=', j, ' datbuf(',k,')=',datbuf(k)
          k=k+1
40
       continue
50
   continue
     status = SWdetach(SWid simple)
     print *,' Value returned by SWdetach = ',status
C -----
     3.1 Define a longitude-latitude box region for the named swath
C -----
    corlat(1) = 37.0
    corlat(2) = 38.5
     corlon(1) = 76.0
     corlon(2) = 77.5
     regionID = SWdefboxreg(SWid index, corlon, corlat, HDFE MIDPOINT)
    print *,' Region ID returned by SWdefboxregion = ', regionID
     3.2 Retrieve information about the subsetted region
        for the named data field
c -----
    status = SWreginfo(SWid index, regionID, "Fakedata", numtype, rank,
    > dims, size)
    print *,' Status returned by SWregioninfo = ', status
```

6.2 Grid Examples

This section contains several examples of the use of the Grid interface from both C and FORTRAN programs. First, there are simple examples in C and FORTRAN which demonstrate the use of most of the functions in the Grid interface.

6.2.1 Creating a Simple Grid

The following C and FORTRAN programs each create, define, and write a simple Grid data set to an HDF-EOS file using the HDF-EOS Grid interface.

6.2.1.1 A C Example of a Simple Grid Creation

```
int
              i, cnt, zonecode, attr[4] = \{11, 33, 66, 99\};
int32 t index1 = 0, index2 = 0;
float32 utmray[60][80], ray2[155][40], ray3[25][80];
float32 psray[360][90], gooderay[120][60];
float32 utmhght[80], georay[60][80];
float32 gooderay2[45][60], psray2[75][90];
float32 lamazray2[65][180], georay2[85][80];
float32 utmcnt = -799.0, ray3cnt = -19.5;
float32 pscnt = -134.5, goodecnt = 27.4;
float32 hghtinit = 323.0, lamazcnt = -299.5, geocnt = 2001.0;
       attr2[5] = \{5.1, 17.2, 28.3, 39.4, 57.5\};
float
int32
       spherecode, xdim, ydim, ray[8];
hssize t
            start[2] = \{10, 10\};
hsize t stride[2] = \{1, 1\};
hsize t edge[2] = \{10, 10\};
hsize t intattr[1] = \{4\};
hsize t floatattr[1] = \{5\};
hsize_t *attrcount = (hsize_t *)NULL;
float64 projparm[16], uplft[2], lowrgt[2];
float64 lonval[5], latval[5];
float64 *datbuf = (float64 *)NULL;
float64 utmtmeray[4800], tmeinit = 35232487.2;
/* ----- */
/*
   Populate data arrays */
/* ----- */
while(index1 < 60) {</pre>
  while (index2 < 80) {
     utmray[index1][index2] = utmcnt;
     georay[index1][index2] = geocnt;
     index2++;
     utmcnt = utmcnt + 0.4;
     geocnt = geocnt + 0.2;
  index1++;
  index2 = 0;
index1=0;
while (index1 < 4800) {
  utmtmeray[index1] = tmeinit;
   index1++;
   tmeinit = tmeinit + 70.7;
```

```
index1=0;
while(index1 < 80) {</pre>
   utmhght[index1] = hghtinit;
   hghtinit = hghtinit + 2.75;
   index1++;
index1=0;
index2=0;
while (index1 < 85) {
   while(index2 < 80) {</pre>
      georay2[index1][index2] = geocnt;
      index2++;
      geocnt = geocnt - .9;
   index1++;
   index2 = 0;
index1=0;
index2=0;
while (index1 < 25) {
   while (index2 < 90) {
      ray3[index1][index2] = ray3cnt;
      index2++;
      ray3cnt=ray3cnt + .1;
   index1++;
   index2 = 0;
index1=0;
index2=0;
while(index1 < 360) {
   while (index2 < 90) {
      psray[index1][index2] = pscnt;
      index2++;
      pscnt = pscnt + .4;
   index1++;
   index2 = 0;
}
index1=0;
index2=0;
while (index1 < 75) {
   while (index2 < 90) {
      psray2[index1][index2] = pscnt;
      index2++;
      pscnt = pscnt - .4;
   index1++;
   index2 = 0;
index1=0;
index2=0;
```

```
while (index1 < 120) {
  while(index2 < 60) {
     gooderay[index1][index2] = goodecnt;
     index2++;
     goodecnt = goodecnt + .4;
  index1++;
  index2 = 0;
}
index1=0;
index2=0;
while (index1 < 45) {
  while (index2 < 60) {
     gooderay2[index1][index2] = goodecnt;
     index2++;
     goodecnt = goodecnt - .4;
  index1++;
  index2 = 0;
}
index1=0;
index2=0;
while(index1 < 65) {</pre>
  while(index2 < 180) {</pre>
     lamazray2[index1][index2] = lamazcnt;
     index2++;
     lamazcnt = lamazcnt + .6;
  index1++;
  index2 = 0;
index1=0;
while(index1 < 16) {
  iprojparm[index1] = 0.0;
  index1++;
/* ----- */
/* Open HDF-EOS file "Grid.h5" (if the named */
/* file does not exist, it will be automatically */
/* created with the read/write access mode */
/* -----*/
gdfid = GDopen("Grid.h5", H5F ACC TRUNC);
          Create UTM grid */
/* ----- */
xdim = 60;
ydim = 80;
uplft[0] = -512740.28306;
uplft[1] = 2733747.62890;
lowrgt[0] = -12584.57301;
```

```
lowrgt[1] = 1946984.64021;
GDid utm = GDcreate(gdfid, "UTM", xdim, ydim, uplft, lowrgt);
/* ----- */
/* Create Geographic grid
xdim = 60;
ydim = 80;
uplft[0] = -126000000.00;
uplft[1] = -064000000.00;
lowrgt[0] = -120000000.00;
lowrgt[1] = -072000000.00;
GDid geo = GDcreate(gdfid, "Geo", xdim, ydim, uplft, lowrgt);
/* ----- */
/* Create Polar Stereo grid of north hemisphere
xdim=360;
ydim=90;
uplft[0] = -10447125.82759;
uplft[1] = 10447125.82759;
lowrgt[0] = 10447125.82759;
lowrgt[1] = -10447125.82759;
gdid_polar_np = GDcreate(gdfid, "Polar_np", xdim, ydim, uplft, lowrgt);
/* ----- */
/* Create Polar Stereo grid of south hemisphere */
/* ----- */
xdim=360;
ydim=90;
uplft[0] = 10447125.82759;
uplft[1] = -10447125.82759;
lowrqt[0] = -10447125.82759;
lowrgt[1] = 10447125.82759;
gdid polar sp = GDcreate(gdfid, "Polar sp", xdim, ydim, uplft, lowrgt);
/* ----- */
       Create Interrupted Goode grid
xdim=120;
ydim=60;
uplft[0] = -11119487.42844;
uplft[1] = 8673539.24806;
lowrqt[0] = 15567282.39984;
lowrgt[1] = -8673539.24806;
GDid igoode = GDcreate(gdfid, "IGoode", xdim, ydim, uplft, lowrgt);
/* ----- */
/* Create Space Oblique Mercator grid */
/* ----- */
```

```
xdim=359;
ydim=321;
uplft[0] = 49844710.48057;
uplft[1] = 884884.39883;
lowrgt[0] = 30521379.68485;
lowrgt[1] = 1152027.64253;
GDid som = GDcreate(gdfid, "SOM", xdim, ydim, uplft, lowrgt);
/* ----- */
/* Create Lambert Azimuthal grid */
xdim=719;
ydim=180;
uplft[0] = 0.0000;
uplft[1] = 9009950.36324;
lowrgt[0] = 0.0000;
lowrgt[1] = -9009950.36324;
GDid lamaz = GDcreate(gdfid, "Lamaz", xdim, ydim, uplft, lowrgt);
/* ----- */
/* Create Hotin Oblique Mercator grid */
xdim=200;
ydim=90;
uplft[0] = 3422259.57265;
uplft[1] = 6824822.05796;
lowrgt[0] = -17519429.48100;
lowrgt[1] = 4994368.88166;
GDid hom = GDcreate(gdfid, "hom", xdim, ydim, uplft, lowrgt);
/* ----- */
/* Create Lambert Conformal grid */
xdim=351;
ydim=171;
uplft[0] = -2279109.37671;
uplft[1] = 12358083.24054;
lowrgt[0] = -56342817.96247;
lowrgt[1] = -24776979.34092;
GDid lamcon = GDcreate(gdfid, "lamcon", xdim, ydim, uplft, lowrgt);
/* ----- */
/* Create Transverse Mercator grid */
/* ----- */
xdim=181;
ydim=171;
uplft[0] = 4855670.77539;
uplft[1] = 9458558.92483;
lowrgt[0] = 5201746.43983;
lowrgt[1] = -10466077.24942;
```

```
GDid tm = GDcreate(gdfid, "tm", xdim, ydim, uplft, lowrgt);
/* Create Polyconic grid */
xdim=161;
ydim=171;
uplft[0] = -250873.85859;
uplft[1] = 12669051.66767;
lowrgt[0] = 850873.85859;
lowrgt[1] = -7137259.12615;
GDid poly = GDcreate(gdfid, "poly", xdim, ydim, uplft, lowrgt);
             Create IS grid
xdim=351;
ydim=171;
uplft[0] = 1436267.12618;
uplft[1] = 9451564.31420;
lowrgt[0] = 1343604.73094;
lowrgt[1] = -9451564.31420;
GDid is = GDcreate(gdfid, "is", xdim, ydim, uplft, lowrgt);
/* ----- */
         Define projections
/* ----- */
zonecode = -13;
spherecode = 0;
for(i=0; i < 16; i++)
  projparm[i]=0.;
status = GDdefproj(GDid utm, GCTP UTM, zonecode, spherecode, projparm);
for(i=0; i < 16; i++)
  projparm[i]=0.;
spherecode = 0;
projparm[5] = 40000000.00;
status=GDdefproj(GDid polar np, GCTP PS, NULL, spherecode, projparm);
for (i=0; i < 16; i++)
  projparm[i] = 0.;
```

```
status=GDdefproj(GDid_igoode, GCTP_GOOD, NULL, NULL, projparm);
for (i=0; i < 16; i++)
   projparm[i]=0.;
status=GDdefproj(GDid lamaz, GCTP LAMAZ, NULL, NULL, projparm);
for(i=0; i < 16; i++)
   projparm[i] = 0.;
projparm[2] = 3;
projparm[3] = 150;
projparm[12] = 1;
status=GDdefproj(GDid som, GCTP SOM, NULL, NULL, projparm);
status=GDdefproj(GDid geo, GCTP GEO, NULL, NULL, NULL);
for (i=0; i < 16; i++)
   projparm[i] = 0.;
              = 0.9996;
projparm[2]
projparm[5]
             = 20000000.00;
             = -75000000.00;
projparm[8]
            = 10000000.00;
projparm[9]
             = -95000000.00;
projparm[10]
projparm[11] = 30000000.00;
status=GDdefproj(GDid hom, GCTP HOM, NULL, NULL, projparm);
for (i=0; i < 16; i++)
   projparm[i] = 0.;
projparm[2] = 20000000.00;
projparm[3] = 40000000.00;
projparm[4] = -75000000.00;
status=GDdefproj(GDid_lamcon, GCTP_LAMCC, NULL, NULL, projparm);
for (i=0; i < 16; i++)
   projparm[i] = 0.;
projparm[2] = 0.9996;
projparm[4] = -75000000.00;
projparm[6] = 5000000.00;
status=GDdefproj(GDid tm, GCTP TM, NULL, NULL, projparm);
for(i=0; i < 16; i++)
   projparm[i] = 0.;
```

```
projparm[4] = 75000000.00;
projparm[5] = -25000000.00;
projparm[6] = 300000.00;
status=GDdefproj(GDid poly, GCTP POLYC, NULL, NULL, projparm);
for (i=0; i < 16; i++)
  projparm[i] = 0.;
projparm[4] = 0.;
projparm[5] = 40000000.00;
status=GDdefproj(GDid is, GCTP ISINUS, NULL, NULL, projparm);
/* Define pixel registration in the grids */
/* ----- */
status = GDdefpixreg(GDid_utm, HDFE CORNER);
status = GDdefpixreg(GDid polar np, HDFE CORNER);
status = GDdefpixreg(GDid igoode, HDFE CORNER);
status = GDdefpixreg(GDid som, HDFE CORNER);
status = GDdefpixreg(GDid_lamaz, HDFE_CORNER);
status = GDdefpixreg(GDid geo, HDFE CORNER);
  Define origin of projections in the grids */
/* ----- */
status = GDdeforigin(GDid utm, HDFE GD UL);
status = GDdeforigin(GDid polar np, HDFE GD UR);
status = GDdeforigin(GDid igoode, HDFE GD LL);
status = GDdeforigin(GDid som, HDFE GD LR);
status = GDdeforigin(GDid lamaz, HDFE GD UL);
status = GDdeforigin(GDid_geo, HDFE_GD_UR);
          Define dimensions
/*
/* ----- */
status = GDdefdim(GDid_utm, "Conduction", 25);
status = GDdefdim(GDid_utm, "Timedim", 4800);
status = GDdefdim(GDid utm, "Hghtdim", 80);
status = GDdefdim(GDid_polar_np, "Convection", 75);
status = GDdefdim(GDid igoode, "Radiant", 45);
status = GDdefdim(GDid som, "Emission", 55);
status = GDdefdim(GDid lamaz, "Flux", 65);
status = GDdefdim(GDid_geo, "Gradient", 85);
  Detach from the grids */
/*
/* ----- */
status = GDdetach(GDid utm);
status = GDdetach(gdid_polar_np);
status = GDdetach(GDid_polar_sp);
status = GDdetach(GDid igoode);
```

```
status = GDdetach(GDid som);
  status = GDdetach(GDid lamaz);
   status = GDdetach(GDid geo);
   status = GDdetach(GDid hom);
  status = GDdetach(GDid lamcon);
   status = GDdetach(GDid tm);
  status = GDdetach(GDid poly);
  status = GDdetach(GDid is);
   /* ----- */
      Re-attach to the grids
  GDid utm = GDattach(gdfid, "UTM");
  GDid_igoode = GDattach(gdfid, "IGoode");
GDid_lamaz = GDattach(gdfid, "Lamaz");
  GDid_polar_np = GDattach(gdfid, "Polar_np");
GDid_som = GDattach(gdfid, "SOM");
GDid_geo = GDattach(gdfid, "Geo");
   /* ----- */
   /* Define data fields for the grids
   /* ----- */
  status = GDdeffield(GDid_utm, "Voltage",
"XDim, YDim", NULL, H5T NATIVE FLOAT, HDFE AUTOMERGE);
   status = GDdeffield (GDid utm, "Drift", "XDim, YDim", NULL, H5T NATIVE FLOAT,
HDFE AUTOMERGE);
  status = GDdeffield(GDid utm, "Time", "Timedim", NULL, H5T NATIVE DOUBLE,
HDFE AUTOMERGE);
   status = GDdeffield(GDid utm, "Height", "Hghtdim", NULL, H5T NATIVE FLOAT,
HDFE AUTOMERGE);
   status = GDdeffield(GDid utm, "Impedance", "XDim, YDim",
NULL, H5T NATIVE FLOAT, HDFE AUTOMERGE);
   status = GDdeffield (GDid utm, "Grounding", "Conduction, YDim",
NULL, H5T NATIVE FLOAT, HDFE NOMERGE);
  status = GDdeffield(GDid_igoode, "SensorG",
"XDim, YDim", NULL, H5T NATIVE FLOAT, HDFE NOMERGE);
   status = GDdeffield(GDid igoode, "VoltageA",
"Radiant, YDim", NULL, H5T_NATIVE_FLOAT, HDFE_NOMERGE);
  status = GDdeffield(GDid polar np, "Bypass",
"XDim, YDim", NULL, H5T_NATIVE_FLOAT, HDFE_NOMERGE);
  status = GDdeffield(GDid_lamaz, "Temperature", "Flux,YDim",
NULL, H5T NATIVE FLOAT, HDFE NOMERGE);
  status = GDdeffield(GDid geo, "Depth", "XDim, YDim", NULL, H5T NATIVE FLOAT,
HDFE NOMERGE);
  status = GDdeffield(GDid geo, "Interval", "Gradient, YDim",
NULL, H5T NATIVE FLOAT, HDFE NOMERGE);
  status = GDdetach(GDid_utm);
  GDid utm = GDattach(gdfid, "UTM");
   /* Write in data to the data fields
   /* ----- */
   status = GDwritefield(GDid utm, "Voltage", start, stride, edge, utmray);
```

```
status = GDwritefield(GDid_utm, "Drift", start, NULL, edge, utmray);
   start[0] = 0;
   edge[0] = 4800;
   status = GDwritefield(GDid utm, "Time", start, NULL, edge, utmtmeray);
   start[0] = 0;
  edge[0] = 80;
   status = GDwritefield(GDid utm, "Height", start, NULL, edge, utmhght);
   start[0] = 0;
   start[1] = 0;
  edge[0] = 60;
  edge[1] = 80;
  status = GDwritefield(GDid_utm, "Impedance", start, NULL, edge, utmray);
  start[0] = 0;
  edge[0] = 25;
  start[1] = 0;
  edge[1] = 80;
  status = GDwritefield(GDid utm, "Grounding", start, NULL, edge, ray3);
  start[0] = 0;
  edge[0] = 80;
  start[1] = 0;
  edge[1] = 60;
  status = GDwritefield(GDid igoode, "SensorG", start, NULL, edge,
gooderay);
  start[0] = 0;
  start[1] = 0;
  edge[0] = 45;
  edge[1] = 60;
  status = GDwritefield(GDid igoode, "VoltageA", start, NULL, edge,
gooderay2);
  start[0] = 0;
  start[1] = 0;
  edge[0] = 60;
  edge[1] = 80;
   status = GDwritefield(GDid polar np, "Bypass", start, NULL, edge, psray);
   start[0] = 0;
   start[1] = 0;
  edge[0] = 65;
  edge[1] = 80;
```

```
status = GDwritefield(GDid_lamaz, "Temperature", start, NULL, edge,
lamazray2);
  start[0] = 0;
  start[1] = 0;
  edge[0] = 60;
  edge[1] = 80;
  status = GDwritefield(GDid geo, "Depth", start, NULL, edge, georay);
  start[0] = 0;
  start[1] = 0;
  edge[0] = 85;
  edge[1] = 80;
  status = GDwritefield(GDid geo, "Interval", start, NULL, edge, georay2);
  /* ----- */
  /* Write attributes for the UTM grid
  /* ----- */
  status = GDwriteattr(GDid utm, "Resistance", H5T NATIVE INT, intattr,
  status = GDwriteattr(GDid_utm, "Current", H5T_NATIVE_FLOAT, floatattr,
attr2);
          Detach from the grids
  /* ----- */
  status = GDdetach(GDid utm);
  status = GDdetach(GDid polar np);
  status = GDdetach(GDid igoode);
  status = GDdetach(GDid som);
  status = GDdetach(GDid lamaz);
  status = GDdetach(GDid_geo);
  /* ----- */
  /* Close the file "Grid.h5" */
  /* ----- */
  status = GDclose(qdfid);
```

6.2.1.2 A FORTRAN Example of a Simple Grid Creation

```
C Simple driver to create and write data
C to the HDF-EOS grid file
C program testgrid

implicit none
integer status
```

```
gdfid
integer
integer
               dummy
               GDid utm, GDid igoode, GDid polar np
integer*4
integer*4
               GDid polar sp
               \operatorname{GDid\_geo}, \operatorname{\overline{G}Did\_som}, \operatorname{GDid} lamaz, \operatorname{GDid} hom
integer*4
integer*4
              GDid lamcon, GDid tm, GDid poly, GDid is
integer
               i, attr(4)
integer*4
              zonecode
integer*4
              index1, index2
              utmray(60,80), ray3(25,80)
real*4
              psray(360,90), gooderay(120,60)
real*4
real*4
              utmhght(80), georay(60,80)
real*4
               gooderay2(45,60), psray2(75,90)
real*4
              lamazray2(65,180), georay2(85,80)
real*4
              utmcnt, ray3cnt
real*4
              pscnt, goodecnt
real*4
              hghtinit, lamazcnt, geocnt
real*4
              attr2(5)
integer*4
              spherecode, xdim, ydim
integer*4
              start(2)
integer*4
               stride(2)
integer*4
               edge (2)
integer*4
               intattr(1)
               floatattr(1)
integer*4
real*8
              projparm(16), uplft(2), lowrgt(2)
real*8
              utmtmeray(4800), tmeinit
integer
               gdopen, gdcreate, gdattach
               gddefproj, gddefdim, gddeffld, gddetach
integer
integer
              qdclose
              gdwrfld, gdwrattr, gddeforigin
integer
integer
              gddefpreg
              H5F ACC RDONLY
integer
               (H5\overline{F} \ ACC \ RDONLY = 0)
parameter
integer
              H5F ACC RDWR
parameter
              (H5F\_ACC\_RDWR = 1)
             H5F ACC TRUNC
integer
              (H5\overline{F} \ AC\overline{C} \ TRUNC = 2)
parameter
             H5F ACC DEBUG
integer
              (H5F ACC DEBUG = 8)
parameter
             H5F ACC EXCL
integer
              (H5\overline{F} \ AC\overline{C} \ EXCL = 4)
parameter
              H5T NATIVE FLOAT
integer
              (H5\overline{T} NATIV\overline{E} FLOAT = 1)
parameter
              H5T NATIVE INT
integer
              (H5T NATIVE INT = 0)
parameter
              H5T NATIVE DOUBLE
integer
parameter
              (H5T_NATIVE_DOUBLE = 2)
              HDFE AUTOMERGE
integer
parameter
              (HDFE AUTOMERGE = 1)
```

```
HDFE NOMERGE
integer
            (HDFE\ NOMERGE = 0)
parameter
            HDFE CENTER
integer
            (HDFE CENTER = 0)
parameter
            HDFE CORNER
integer
            (HDFE CORNER = 1)
parameter
            HDFE_GD_UL
integer
            (HDFE GD UL = 0)
parameter
            HDFE GD UR
integer
            (HDFE GD UR = 1)
parameter
            HDFE GD LL
integer
parameter
            (HDFE GD LL = 2)
            HDFE GD LR
integer
            (HDFE GD LR = 3)
parameter
             HDFE NENTDIM
integer
             (HDFE NENTDIM = 0)
parameter
            HDFE NENTDFLD
integer
             (HDFE\ NENTDFLD = 4)
parameter
             HDFE NOPREVSUB
integer
            (HDFE NOPREVSUB = -1)
parameter
             GCTP GEO
integer
             (GCTP GEO = 0)
parameter
             GCTP UTM
integer
             (GCTP UTM = 1)
parameter
             GCTP LAMCC
integer
            (GCTP LAMCC = 4)
parameter
integer
             GCTP PS
parameter
             (GCTP PS = 6)
             GCTP POLYC
integer
parameter
            (GCTP\_POLYC = 7)
             GCTP TM
integer
            (GCTP TM = 9)
parameter
             GCTP LAMAZ
integer
            (GCTP LAMAZ = 11)
parameter
             GCTP HOM
integer
             (GCTP HOM = 20)
parameter
             GCTP SOM
integer
             (GCTP SOM = 22)
parameter
             GCTP GOOD
integer
             (GCTP GOOD = 24)
parameter
             GCTP ISINUS
integer
parameter
             (GCTP_ISINUS = 99)
status = -1
attr(1) = 11
attr(2) = 33
attr(3) = 66
attr(4) = 99
attr2(1) = 5.1
attr2(2) = 17.2
attr2(3) = 28.3
attr2(4) = 39.4
attr2(5) = 57.5
start(1) = 10
```

```
start(2) = 10
     stride(1) = 1
     stride(2) = 1
     edge(1) = 10
     edge(2) = 10
     intattr(1) = 4
     floatattr(1) = 5
     tmeinit = 35232487.2
     geocnt = 2001.0
goodecnt = 27.4
lamazcnt = -299.5
hghtinit = 323.0
pscnt = -134.5
                = -799.0
     utmcnt
     ray3cnt = -19.5
C ------
С
        Populate data arrays
     do 20 index1 =1, 60
        do 10 index2 =1, 80
           utmray(index1,index2) = utmcnt
           georay(index1,index2) = geocnt
           utmcnt = utmcnt + 0.4
           geocnt = geocnt + 0.2
10
        continue
20
     continue
     do 30 index1 =1,4800
        utmtmeray(index1) = tmeinit
        tmeinit = tmeinit + 70.7
30
     continue
     do 40 index1 =1, 80
        utmhght(index1) = hghtinit
        hghtinit = hghtinit + 2.75
40
     continue
     do 60 index1 =1, 85
        do 50 index2 =1, 80
           georay2(index1,index2) = geocnt
           geocnt = geocnt - .9
50
        continue
60
     continue
     do 80 index1 =1, 25
        do 70 index2 =1, 90
           ray3(index1,index2) = ray3cnt
           ray3cnt=ray3cnt + .1
70
        continue
80
     continue
     do 100 index1 =1, 360
        do 90 index2 =1, 90
```

```
psray(index1,index2) = pscnt
          pscnt = pscnt + .4
90
        continue
100 continue
     do 120 index1 =1, 75
        do 110 index2 =1, 90
          psray2(index1,index2) = pscnt
          pscnt = pscnt - .4
110
        continue
120 continue
     do 140 index1 =1, 120
       do 130 index2 =1, 60
          gooderay(index1,index2) = goodecnt
          goodecnt = goodecnt + .4
130
        continue
140 continue
     do 160 index1 =1, 45
        do 150 index2 =1, 60
          gooderay2(index1,index2) = goodecnt
          goodecnt = goodecnt - .4
150
        continue
160 continue
     do 240 index1 =1, 65
        do 230 index2 =1, 180
          lamazray2(index1,index2) = lamazcnt
          lamazcnt = lamazcnt + .6
230
       continue
240 continue
     do 250 index1 =1, 16
       projparm(index1) = 0.0
250 continue
    Open HDF-EOS file "Grid.h5" (if the named
   file does not exist, it will be automatically
С
     created with the read/write access mode
С
  ______
     gdfid = GDopen("Grid.h5", H5F_ACC_TRUNC)
C ------
                 Create UTM grid
С
     xdim = 60
     ydim = 80
     uplft(1) = -512740.28306
     uplft(2) = 2733747.62890
     lowrgt(1) = -12584.57301
     lowrgt(2) = 1946984.64021
     GDid_utm = GDcreate(gdfid, "UTM", xdim, ydim, uplft, lowrgt)
```

```
Create Geographic grid
С
     xdim = 60
     ydim = 80
     uplft(1) = -126000000.00
     uplft(2) = -064000000.00
     lowrgt(1) = -120000000.00
     lowrgt(2) = -072000000.00
     GDid geo = GDcreate(gdfid, "Geo", xdim, ydim, uplft, lowrgt)
    Create Polar Stereo grid of north hemisphere
 ______
     xdim=360
     ydim=90
     uplft(1)
             = -10447125.82759
     uplft(2) = 10447125.82759
     lowrgt(1) = 10447125.82759
     lowrgt(2) = -10447125.82759
     gdid polar np = GDcreate(gdfid, "Polar np", xdim, ydim, uplft,
         lowrgt)
    Create Polar Stereo grid of south hemisphere
  ______
     xdim=360
     ydim=90
     uplft(1) = 10447125.82759
     uplft(2) = -10447125.82759
     lowrgt(1) = -10447125.82759
     lowrqt(2) = 10447125.82759
     gdid polar sp = GDcreate(gdfid, "Polar sp", xdim, ydim, uplft,
         lowrgt)
С
           Create Interrupted Goode grid
     xdim=120
     ydim=60
     uplft(1) = -11119487.42844
     uplft(2) = 8673539.24806
     lowrgt(1) = 15567282.39984
     lowrgt(2) = -8673539.24806
     GDid igoode = GDcreate(gdfid, "IGoode", xdim, ydim, uplft,
     1 lowrgt)
   Create Space Oblique Mercator grid
```

```
xdim=359
     ydim=321
     uplft(1) = 49844710.48057
     uplft(2) = 884884.39883
     lowrgt(1) = 30521379.68485
     lowrgt(2) = 1152027.64253
     GDid som = GDcreate(gdfid, "SOM", xdim, ydim, uplft, lowrgt)
 ______
С
          Create Lambert Azimuthal grid
     xdim=719
     ydim=180
     uplft(1) = 0.0000
     uplft(2) = 9009950.36324
     lowrgt(1) = 0.0000
     lowrgt(2) = -9009950.36324
     GDid lamaz = GDcreate(gdfid, "Lamaz", xdim, ydim, uplft, lowrgt)
C ------
   Create Hotin Oblique Mercator grid
C
     xdim=200
     ydim=90
     uplft(1) = 3422259.57265
     uplft(2) = 6824822.05796
     lowrgt(1) = -17519429.48100
     lowrgt(2) = 4994368.88166
     GDid hom = GDcreate(gdfid, "hom", xdim, ydim, uplft, lowrgt)
 ______
С
         Create Lambert Conformal grid
C
     xdim=351
     ydim=171
     uplft(1)
             = -2279109.37671
     uplft(2) = 12358083.24054
     lowrgt(1) = -56342817.96247
     lowrgt(2) = -24776979.34092
     GDid lamcon = GDcreate(gdfid, "lamcon", xdim, ydim, uplft,
        lowrgt)
          Create Transverse Mercator grid
     xdim=181
     ydim=171
     uplft(1) = 4855670.77539
     uplft(2) = 9458558.92483
     lowrgt(1) = 5201746.43983
```

```
lowrgt(2) = -10466077.24942
     GDid tm = GDcreate(gdfid, "tm", xdim, ydim, uplft, lowrgt)
               Create Polyconic grid
     xdim=161
     ydim=171
     uplft(1) = -250873.85859
     uplft(2) = 12669051.66767
     lowrgt(1) = 850873.85859
     lowrgt(2) = -7137259.12615
     GDid_poly = GDcreate(gdfid, "poly", xdim, ydim, uplft, lowrgt)
              Create IS grid
 -----
     xdim=351
     ydim=171
     uplft(1) = 1436267.12618
     uplft(2) = 9451564.31420
     lowrgt(1) = 1343604.73094
     lowrgt(2) = -9451564.31420
     GDid is = GDcreate(gdfid, "is", xdim, ydim, uplft, lowrgt)
C ------
            Define projections
С
     zonecode = -13
     spherecode = 0
     do 260 i=1,16
       projparm(i)=0.
260 continue
     status = GDdefproj(GDid utm, GCTP UTM, zonecode, spherecode,
     1 projparm)
     do 270 i=1,16
       projparm(i)=0.
270 continue
     spherecode = 0
     projparm(6) = 40000000.00
     status=GDdefproj(GDid polar np, GCTP PS, dummy, spherecode,
     1 projparm)
     do 280 i=1,16
       projparm(i)=0.
280 continue
```

```
status=GDdefproj(GDid igoode, GCTP GOOD, dummy, dummy, projparm)
     do 290 i=1,16
       projparm(i)=0.
290 continue
     status=GDdefproj(GDid lamaz, GCTP LAMAZ, dummy, dummy, projparm)
     do 300 i=1,16
       projparm(i)=0.
300 continue
    projparm(3) = 3
     projparm(4) = 150
    projparm(13) = 1
     status=GDdefproj(GDid som, GCTP SOM, dummy, dummy, projparm)
     status=GDdefproj(GDid geo, GCTP GEO, dummy, dummy, dummy)
     do 310 i=1,16
       projparm(i)=0.
310 continue
                      = 0.9996
    projparm(3)
                      = 2000000.00
    projparm(6)
    projparm(9)
                      = -75000000.00
    projparm(10)
                      = 10000000.00
                      = -95000000.00
    projparm(11)
                      = 3000000.00
    projparm(12)
     status=GDdefproj(GDid hom, GCTP HOM, dummy, dummy, projparm)
     do 320 i=1,16
       projparm(i)=0.
320 continue
     projparm(3) = 20000000.00
     projparm(4) = 40000000.00
    projparm(5) = -75000000.00
     status=GDdefproj(GDid_lamcon, GCTP_LAMCC, dummy, dummy, projparm
     1 )
     do 330 i=1,16
       projparm(i)=0.
330 continue
     projparm(3) = 0.9996
    projparm(5) = -75000000.00
    projparm(7) = 5000000.00
     status=GDdefproj(GDid tm, GCTP TM, dummy, dummy, projparm)
     do 340 i=1,16
       projparm(i)=0.
```

```
340 continue
    projparm(5) = 75000000.00
    projparm(6) = -25000000.00
    projparm(7) = 300000.00
    status=GDdefproj(GDid_poly, GCTP_POLYC, dummy, dummy, projparm)
    do 350 i=1,16
       projparm(i)=0.
350 continue
    projparm(5) = 0.
    projparm(6) = 40000000.00
     status=GDdefproj(GDid is, GCTP ISINUS, dummy, dummy, projparm)
     Define pixel registration in the grids
    status = GDdefpreg(GDid utm, HDFE CORNER)
    status = GDdefpreg(GDid polar np, HDFE CORNER)
    status = GDdefpreg(GDid igoode, HDFE CORNER)
    status = GDdefpreg(GDid_som, HDFE_CORNER)
    status = GDdefpreg(GDid lamaz, HDFE CORNER)
    status = GDdefpreg(GDid geo, HDFE CORNER)
  Define origin of projections in the grids
 ______
    status = GDdeforigin(GDid utm, HDFE GD UL)
    status = GDdeforigin(GDid polar np, HDFE GD UR)
    status = GDdeforigin(GDid igoode, HDFE GD LL)
    status = GDdeforigin(GDid som, HDFE GD LR)
    status = GDdeforigin(GDid_lamaz, HDFE_GD_UL)
    status = GDdeforigin(GDid geo, HDFE GD UR)
               Define dimensions
    status = GDdefdim(GDid_utm, "Conduction", 25)
    status = GDdefdim(GDid_utm, "Timedim", 4800)
    status = GDdefdim(GDid_utm, "Hghtdim", 80)
    status = GDdefdim(GDid polar np, "Convection", 75)
    status = GDdefdim(GDid igoode, "Radiant", 45)
    status = GDdefdim(GDid som, "Emission", 55)
    status = GDdefdim(GDid_lamaz, "Flux", 65)
    status = GDdefdim(GDid_geo, "Gradient", 85)
              Detach from the grids
    status = GDdetach(GDid utm)
    status = GDdetach(gdid polar np)
    status = GDdetach(GDid polar sp)
```

6-40

```
status = GDdetach(GDid igoode)
   status = GDdetach(GDid som)
   status = GDdetach(GDid lamaz)
   status = GDdetach(GDid geo)
   status = GDdetach(GDid hom)
   status = GDdetach(GDid_lamcon)
   status = GDdetach(GDid tm)
   status = GDdetach(GDid poly)
   status = GDdetach(GDid is)
_____
             Re-attach to the grids
   GDid_utm
                 = GDattach(gdfid, "UTM")
   GDid_igoode = GDattach(gdfid, "IGoode")

GDid_lamaz = GDattach(gdfid, "Lamaz")

GDid_polar_np = GDattach(gdfid, "Polar_np")

GDid_som = GDattach(gdfid, "SOM")

GDid_geo = GDattach(gdfid, "Geo")
     Define data fields for the grids
   status = GDdeffld(GDid utm, "Voltage", "XDim,YDim",""
   1 , H5T NATIVE FLOAT, HDFE AUTOMERGE)
    status = GDdeffld(GDid utm, "Drift", "XDim, YDim",""
    1 , H5T NATIVE FLOAT, HDFE AUTOMERGE)
   status = GDdeffld(GDid_utm, "Time", "Timedim",""
   1 , H5T NATIVE DOUBLE, HDFE AUTOMERGE)
    status = GDdeffld(GDid utm, "Height", "Hghtdim",""
    1 , H5T NATIVE FLOAT, HDFE AUTOMERGE)
    status = GDdeffld(GDid utm, "Impedance", "XDim, YDim", ""
         ,H5T NATIVE FLOAT,HDFE AUTOMERGE)
    status = GDdeffld(GDid utm, "Grounding", "Conduction, YDim",
         "", H5T_NATIVE_FLOAT, HDFE_NOMERGE)
    status = GDdeffld(GDid igoode, "SensorG", "XDim, YDim", ""
        ,H5T NATIVE FLOAT, HDFE NOMERGE)
    status = GDdeffld(GDid_igoode, "VoltageA", "Radiant, YDim", ""
       ,H5T NATIVE FLOAT, HDFE NOMERGE)
    status = GDdeffld(GDid polar np, "Bypass", "XDim, YDim", ""
      ,H5T_NATIVE_FLOAT, HDFE_NOMERGE)
    status = GDdeffld(GDid lamaz, "Temperature", "Flux, YDim", ""
    1 , H5T NATIVE FLOAT, HDFE NOMERGE)
    status = GDdeffld(GDid geo, "Depth", "XDim, YDim", ""
        ,H5T NATIVE FLOAT, HDFE NOMERGE)
    status = GDdeffld(GDid geo, "Interval", "Gradient, YDim", ""
         ,H5T_NATIVE_FLOAT, HDFE NOMERGE)
    status = GDdetach(GDid utm)
    GDid utm = GDattach(gdfid, "UTM")
 Write in data to the data fields
```

```
status = GDwrfld(GDid_utm, "Voltage", start, stride, edge,
1 utmray)
status = GDwrfld(GDid utm, "Drift", start, stride, edge,
   utmray)
start(1) = 0
edge(1) = 4800
status = GDwrfld(GDid utm, "Time", start, stride, edge,
1 utmtmeray)
start(1) = 0
edge(1) = 80
status = GDwrfld(GDid utm, "Height", start, stride, edge,
1 utmhght)
start(1) = 0
start(2) = 0
edge(1) = 60
edge(2) = 80
status = GDwrfld(GDid utm, "Impedance", start, stride, edge,
   utmray)
start(1) = 0
edge(1) = 25
start(2) = 0
edge(2) = 80
status = GDwrfld(GDid utm, "Grounding", start, stride, edge,
1 ray3)
start(1) = 0
edge(1) = 80
start(2) = 0
edge(2) = 60
status = GDwrfld(GDid igoode, "SensorG", start, stride, edge,
1 gooderay)
start(1) = 0
start(2) = 0
edge(1) = 45
edge(2) = 60
status = GDwrfld(GDid_igoode, "VoltageA", start, stride, edge
1 , gooderay2)
start(1) = 0
start(2) = 0
edge(1) = 60
edge(2) = 80
status = GDwrfld(GDid polar np, "Bypass", start, stride, edge
```

```
1 , psray)
    start(1) = 0
    start(2) = 0
    edge(1) = 65
    edge(2)
           = 80
    status = GDwrfld(GDid lamaz, "Temperature", start, stride,
        edge, lamazray2)
    start(1) = 0
    start(2) = 0
    edge(1) = 60
    edge (2) = 80
    status = GDwrfld(GDid geo, "Depth", start, stride, edge,
      georay)
    start(1) = 0
    start(2) = 0
    edge(1) = 85
    edge(2) = 80
    status = GDwrfld(GDid_geo, "Interval", start, stride, edge,
    1 georay2)
    Write attributes for the UTM grid
  ______
    status = GDwrattr(GDid utm, "Resistance", H5T NATIVE INT,
    1 intattr, attr)
    status = GDwrattr(GDid utm, "Current", H5T NATIVE FLOAT,
    floatattr, attr2)
 ______
            Detach from the grids
 ______
    status = GDdetach(GDid utm)
    status = GDdetach(GDid polar np)
    status = GDdetach(GDid_igoode)
    status = GDdetach (GDid som)
    status = GDdetach(GDid lamaz)
    status = GDdetach(GDid geo)
C ------
          Close the file "Grid.h5"
    status = GDclose(gdfid)
    stop
    end
```

6.2.2 Performing Subsetting for a Grid

The following C and FORTRAN programs each demonstrate how to perform subsetting for a Grid object in an HDF-EOS file using the HDF-EOS Grid interface.

6.2.2.1 A C Example of a Subsetting for a Grid

```
/* ----- */
/* Simple driver demonstrating how to perform subsetting along XDim and */
/* YDim for a grid.
/* NOTE: make sure that the HDF-EOS file Gridc Test.h5 produced by the
                                                      */
     test driver testgrid_he3.c exists.
#include "HdfEosDef.h"
main()
  herr t status;
  int
           i;
  int32
          rank, size;
  hsize t dims[8];
  H5T class t *numtype = (H5T class t *) NULL;
  float32 *buffer;
  float64 corlon[2], corlat[2];
float64 iuplft[2], ilowrgt[2];
  iuplft[0] = 0.;
  iuplft[1] = 0.;
  ilowrqt[0] = 0.;
  ilowrqt[1] = 0.;
/* ----- */
  Open grid file "Gridc Test.h5" and attach to the named grid
/* objects.
/* ----- */
  gdfid = GDopen("Gridc_Test.h5", H5F_ACC RDONLY);
  printf("\t\tValue returned by GDopen %d\n\n", gdfid);
  GDid geo = GDattach(gdfid, "Geo");
  printf("\t\tValue returned by GDattach %d\n\n", GDid geo);
/* ----- */
/* Define a longitude-latitude box region for the named grid */
```

```
corlon[0] = -123.5;
  corlon[1] = -121.5;
  corlat[0] = -67.0;
  corlat[1] = -70.0;
  regionID = GDdefboxregion(GDid geo, corlon, corlat);
  printf("\t\tRegion id returned by GDdefboxregion %d\n", regionID);
/* ------ */
       Retrieve information about the subsetted region
/*
        for the named data field
  numtype = (H5T class t *)calloc(1, sizeof(H5T class t));
  status = GDregioninfo(GDid geo,
regionID, "Depth", numtype, &rank, dims, &size, iuplft, ilowrgt);
  printf("\t\tStatus returned by GDregioninfo %d\n", status);
  printf("\t\tNumber type of region %d rank of region %d\n", *numtype, rank);
  printf("\t\tDimension of region %lu %lu Size of region in bytes
%d\n", (unsigned long)dims[0], (unsigned long)dims[1], size);
  printf("\t\tUpper left point %f %f, Lower right point %f
%f\n",iuplft[0],iuplft[1],ilowrgt[0],ilowrgt[1]);
  free (numtype);
/* Read data into the data buffer from the subsetted region */
  buffer = (float32 *)malloc(size);
   status = GDextractregion(GDid geo, regionID, "Depth", buffer);
   printf("\t\tStatus returned by GDextractregion %d\n", status);
    for(i = 0; i < 5; i++)
      printf("\t\tValue of buffer %f\n", buffer[i]);
  free (buffer);
  status = GDdetach(GDid geo);
  printf("\t\tValue returned by GDdetach %d\n\n", status);
  status = GDclose(gdfid);
  printf("\t\tValue returned by GDclose %d\n", status);
6.2.2.2 A FORTRAN Example of a Subsetting for a Grid
c ------
c Simple driver demonstrating how to perform subsetting along XDim and
c YDim for a grid.
c NOTE: make sure that the HDF-EOS file Gridc Test.h5 produced by the
   test driver testgrid he3.c exists.
c ------
     implicit none
integer gdopen,gdattach,gddetach
```

```
integer i
    integer*4 rank, size
    integer*4
              dims(8)
              numtype(1)
    integer
    real*4
              buffer(48000)
    real*8
              corlon(2), corlat(2)
    real*8 real*8
              iuplft(2), ilowrgt(2)
    integer
              H5F ACC RDONLY
    parameter (H5F_ACC_RDONLY = 0)
    iuplft(1) = 0.
    iuplft(2) = 0.
    ilowrgt(1) = 0.
    ilowrgt(2) = 0.
  Open grid file "Gridc Test.h5" and attach to the named grid
С
    objects.
С
             _____
    gdfid = GDopen("Grid.h5", H5F ACC RDONLY)
    print *,' Value returned by GDopen = ', gdfid
    GDid_geo = GDattach(gdfid, "Geo")
    Define a longitude-latitude box region for the named grid
С
    corlon(1) = -123.5
    corlon(2) = -121.5
    corlat(1) = -67.0
    corlat(2) = -70.0
    regionID = GDdefboxreg(GDid_geo,corlon, corlat)
    print *,' Region id returned by GDdefboxregion = ',
     regionID
С
      Retrieve information about the subsetted region
        for the named data field
С
```

```
status = GDreginfo(GDid geo, regionID, "Depth", numtype, rank
   > ,dims,size,iuplft, ilowrgt)
   print *,' Status returned by GDregioninfo = ', status
print *,' Number type of region = ', numtype,
> ' rank of region = ', rank
    print *,' Dimension of region = ', dims(1), dims(2),
   > ' Size of region in bytes = ', size
    print *,' Upper left point = ', iuplft(1),iuplft(2),
      ' Lower right point= ', ilowrgt(1),ilowrgt(2)
    Read data into the data buffer from the subsetted region
______
    status = GDextreg(GDid geo, regionID, "Depth", buffer)
    print *,' Status returned by GDextractregion = ', status
    do 10 i = 1,5
      print *,'
                    Value of buffer ',i, ' is ',buffer(i)
10
   continue
    status = GDdetach(GDid geo)
    print *,' Value returned by GDdetach = ', status
    status = GDclose(gdfid)
    stop
    end
```

6.3 Combining HDF and HDF-EOS Objects

The HDF-EOS structures, swath, point, and grid, are built out of the standard HDF5 objects such as groups, data sets, and attributes and thus an HDF-EOS file can contain both HDF and HDF-EOS entities.

6.3.1 Adding HDF-EOS Structures to an Existing HDF File

In this example we open an existing HDF file, *NativeHDF.hdf*, and add a swath structure. Because the swath is an HDF-EOS entity we use the HDF-EOS API routines to open, create, detach and close, ie, *SWopen, SWcreate, SWdetach*, and *SWclose*.

```
/* Open HDF file for read-write access */
    fileID = SWopen("NativeHDF.hdf", DFACC_RDWR);
    /* Create Swath Structure */
swathID = SWcreate(fileID, "SwathStructure");
/* Detach Swath Structure */
status = SWdetach(swathID);
/* Close File */
status = SWclose(fileID);
);
```

This page intentionally left blank.

7. Writing ODL Metadata into HDF-EOS

7.1 A C Example of Metadata Write

The following C code fragment is an example of how a user can write granule metadata (or inventory metadata) into their HDF-EOS file. The Metadata Configuration File (MCF), which the code accesses is given in section 7.3. The output ODL file which results from running the code in 7.2 is given in section 7.4.

In order to assist a developer of software for producing data in ECS format, a file template called filetable.temp is provided in section 7.5. This file is similar to the Process Control File used by the larger SDP Toolkit, but simpler. It is used to specify the relationship between logical file identifiers used in source code and physical files containing input data or output data. It is also used to specify the IDs for log status reports and for the MCFs.

It should be mentioned that currently only MTD TOOLKIT (a subset of SDP TOOLKIT that handles metadata and Time/Date conversions) has been modified to write metadata into HDF-EOS files utilizing HDF5. Moreover, in the new MTD TOOLKIT for HDF5 some tools, such as PGS_MET_GetPCAttr() and PGS_MET_InitNonMCF() are not available yet. Details on Metadata Configuration Files can be found in the SDP Toolkit Users Guide for ECS project, Section 6.2.1 and Appendix J (33-CD-500-001). Details on how to install and use MTD TOOLKIT tools can be found in Toolkit_MTD Users Guide.

7.2 C Code

```
int main()
/**********************
Declarations.
**********************
   PGSt MET all handles
                         mdHandles;
   PGSt MET all handles
                         handles;
                         fileName1[PGSd MET FILE PATH MAX]="";
   char
   char
                         fileName2[PGSd_MET_FILE_PATH_MAX] = "";
                         my HDF file[PGSd MET FILE PATH MAX]="";
   char
                         msg[PGS_SMF_MAX_MSG_SIZE];
   char
                         mnemonic[PGS SMF MAX MNEMONIC SIZE];
   char
                         fileMessage[PGS SMF MAX MSG SIZE];
   char
   int32 t
                         sdid1;
   PGSt SMF status
                        ret = PGS S SUCCESS;
   char
                         *informationname;
   PGSt integer
                        ival =3;
   PGSt double
                        dval=203.2;
                        fileId, fileId2;
   PGSt integer
   PGSt integer
                        i;
   PGSt integer
                        version;
   PGSt SMF status
                        returnStatus;
                         *mysaval[5];
   char
   /* Associate logical IDs with physical filenames. */
   ret=PGS MET SetFileId();
   printf("ret after PGS MET SetFileId()is %d in Main\n",ret);
   if(ret != PGS S SUCCESS)
    printf(" Failed in assigning logical IDs\n");
   /*recover file name for fileId=PGSd MET MCF FILE */
   version = 1;
   fileId = PGSd MET MCF FILE;
   returnStatus = PGS PC GetReference( fileId, &version,
                         fileName1);
   if ( returnStatus != PGS S SUCCESS )
     PGS SMF GetMsg( &returnStatus, mnemonic, msg);
     strcpy(fileMessage, msg);
     PGS SMF SetDynamicMsg( returnStatus, fileMessage,
                      "metatest" );
   }
   else
   {
```

```
printf("The input file for ID %d is %s\n",fileId,fileName1);
    informationname=(char *) malloc(330);
    /* Initialize MCF file */
    fileId = 10250;
    ret=PGS MET Init(fileId, handles);
    if (ret !=PGS S SUCCESS)
     printf("initialization failed\n");
     return (-1);
   else
     printf("ret after PGS MET Init is %d\n",ret);
    /* test PGS MET SetAttr */
    ival=667788;
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "QAPERCENTINTERPOLATEDDATA.1", &ival);
   printf("ret after SetAttr for QAPERCENTINTERPOLATEDDATA.1 is %d\n",
ret);
    ival=12345;
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "QAPercentMissingData.1", &ival);
    printf("ret after SetAttr for QAPercentMissingData.1 is %d\n",ret);
    ival=123;
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "QAPercentOutofBoundsData.1", &ival);
    printf("ret after SetAttr for QAPercentOutofBoundsData.1 is %d\n", ret);
    ival=23456;
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "QAPercentOutofBoundsData.2", &ival);
    printf("ret after SetAttr for QAPercentOutofBoundsData.1 is %d\n", ret);
    ival=56789;
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "QAPercentMissingData.2", &ival);
    printf("ret after SetAttr for QAPercentMissingData.1 is %d\n",ret);
    strcpy(informationname, "Exercise1");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
            "AutomaticQualityFlagExplanation.1", &informationname);
    printf("ret after SetAttr for AutomaticQualityFlagExplanation.1 is
```

```
%d\n", ret);
    strcpy(informationname, "1997/12/23");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "RangeBeginningDateTime", &informationname);
   printf("ret after SetAttr for RangeBeginningDateTime is %d\n",ret);
    strcpy(informationname, "1997.07/30");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "RangeBeginningDate", &informationname);
    printf("ret after SetAttr for RangeBeginningDate is %d\n",ret);
    strcpy(informationname, "ReprocessingplannINVENT");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "ReprocessingPlanned", &informationname);
   printf("ret after SetAttr for ReprocessingPlanned is %d\n",ret);
    strcpy(informationname,"\"ReprocessingplannARCHIVE");
    ret=PGS MET SetAttr(handles[ARCHIVEDMETADATA],
                  "ReprocessingPlanned", &informationname);
   printf("ret after SetAttr for ReprocessingPlanned is %d\n",ret);
    strcpy(informationname, "Reprocessin");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "ReprocessingActual", &informationname);
   printf("ret after SetAttr for ReprocessingActual is %d\n",ret);
    strcpy(informationname, "ID1111");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "LocalGranuleID", &informationname);
   printf("ret after SetAttr for LocalGranuleID is %d\n",ret);
    strcpy(informationname, "version1234");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "LocalVersionID", &informationname);
   printf("ret after SetAttr for LocalVersionID is %d\n",ret);
    strcpy(informationname, "Flag1");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "DayNightFlag", &informationname);
   printf("ret after SetAttr for DayNightFlag is %d\n",ret);
    strcpy(informationname, "Flag1");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "DayNightFlag", &informationname);
   printf("ret after SetAttr for DayNightFlag is %d\n",ret);
    strcpy(informationname, "information1");
    ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
                  "ParameterName.1", &informationname);
   printf("ret after SetAttr for ParameterName is %d\n", ret);
```

```
strcpy(informationname, "information2");
ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
              "ParameterName.2", &informationname);
printf("ret after SetAttr for ParameterName.2 is %d\n",ret);
strcpy(informationname, "information3");
ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
              "ParameterName.3", &informationname);
printf("ret after SetAttr for ParameterName is %d\n", ret);
strcpy(informationname, "information4");
ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
              "ParameterName.4", &informationname);
printf("ret after SetAttr for ParameterName is %d\n", ret);
dval=111.11;
ret=PGS MET SetAttr(handles[ARCHIVEDMETADATA],
              "WestBoundingCoordinate", &dval);
printf("ret WestBoundingCoordinate is %d %f\n", ret, dval);
dval=222.22;
ret=PGS MET SetAttr(handles[ARCHIVEDMETADATA],
              "northBoundingCoordinate", &dval);
printf("ret northBoundingCoordinate is %d %f\n", ret, dval);
dval=333.33;
ret=PGS MET SetAttr(handles[ARCHIVEDMETADATA],
              "EastBoundingCoordinate", &dval);
printf("ret EastBoundingCoordinate is %d %f\n",ret,dval);
dval=444.44;
ret=PGS MET SetAttr(handles[ARCHIVEDMETADATA],
              "SouthBoundingCoordinate", &dval);
printf("ret SouthBoundingCoordinate is %d %f\n",ret,dval);
dval=11.11;
ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
              "WestBoundingCoordinate", &dval);
printf("ret WestBoundingCoordinate is %d %f\n",ret,dval);
dval=22.22;
ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
             "northBoundingCoordinate", &dval);
printf("ret northBoundingCoordinate is %d %f\n",ret,dval);
dval=33.33;
ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
              "EastBoundingCoordinate", &dval);
printf("ret EastBoundingCoordinate is %d %f\n", ret, dval);
dval=44.44;
ret=PGS MET SetAttr(handles[INVENTORYMETADATA],
```

```
"SouthBoundingCoordinate", &dval);
   printf("ret SouthBoundingCoordinate is %d %f\n",ret,dval);
    /* Get the value of set attribute */
    dval=11.11;
    ret=PGS MET GetSetAttr(handles[INVENTORYMETADATA],
                     "SouthBoundingCoordinate", &dval);
    printf("after GetSetAttr: ret SouthBoundingCoordinate is %d
%f\n", ret, dval);
    /* Get data from config file */
    ret = PGS MET GetConfigData("TEST PARM FLOAT", &dval);
    printf("after PGS MET GetConfigData : ret TEST PARM INT is %d
%f\n",ret, dval);
    /* write metadata to HDF and ASCII files */
    version =1;
    fileId = 5039;
    ret = PGS_PC_GetReference(fileId, &version, my_HDF_file);
   printf("after PGS PC GetReference ret =%d\n",ret);
   printf("after PGS PC GetReference my HDF file = %s\n",my HDF file);
    if (ret == PGS S SUCCESS)
      sdid1=PGS_MET_SDstart(my_HDF_file, H5F ACC RDWR);
      printf("after PGS MET SDstart sdid1 =%d\n", sdid1);
    }
    else
     return (-1);
   printf("After SDstart sdid1 is %d\n", sdid1);
    /**** write INVENTORYMETADATA to HDF file *****/
    ret=PGS MET Write(handles[INVENTORYMETADATA],"coremetadata",sdid1);
    printf("ret after PGS MET Write is %d\n", ret);
    if(ret !=PGS S SUCCESS && ret != PGSMET W METADATA NOT SET)
      if (ret == PGSMET E MAND NOT SET)
         printf("some mandatory parameters were not set\n");
      else
```

```
printf("HDF write failed\n");
  }
/**** write ARCHIVEDMETADAT to HDF file *****/
ret=PGS MET Write(handles[ARCHIVEDMETADATA], "archivemetadata",
printf("ret after PGS MET Write is %d\n",ret);
if(ret !=PGS S SUCCESS && ret != PGSMET W METADATA NOT SET)
  if (ret == PGSMET E MAND NOT SET)
      printf("some mandatory parameters were not set\n");
  }
  else
  {
      printf("HDF write failed\n");
/**** write to non-HDF file *****/
fileId = 5804;
printf("non-hdf file to be written has fileId %d\n", fileId);
ret=PGS MET Write(handles[ODL IN MEMORY], NULL, fileId);
printf("ret after PGS MET Write is %d\n",ret);
if (ret !=PGS S SUCCESS && ret != PGSMET W METADATA NOT SET)
  if (ret == PGSMET E MAND NOT SET)
      printf("some mandatory parameters were not set\n");
  }
  else
      printf("ASCII write failed\n");
}
/**** write to default non-HDF file *****/
ret=PGS MET Write(handles[ODL IN MEMORY], NULL, NULL);
printf("ret after PGS_MET_Write is %d\n",ret);
if (ret !=PGS S SUCCESS && ret != PGSMET W METADATA NOT SET)
  if (ret == PGSMET E MAND NOT SET)
      printf("some mandatory parameters were not set\n");
  }
```

```
else
{
     printf("ASCII write failed\n");
}

(void) PGS_MET_SDend(sdid1);

PGS_MET_Remove();
free(informationname);

printf("Complete...\n");
return 0;
}
```

7.3 The Metadata Configuration File (MCF) for Code in Section 7.2

```
/********************
/*
                                                       */
/*
  This is a working version of the MCF template that will be
                                                       * /
/* supplied with the next SDP Toolkit. This MCF template will */
/* NOT be official until the SDP Toolkit is released. All
                                                       */
/* details are subject to change.
                                                       */
                                                       * /
/* This MCF file represents the ODL which is expected to be
                                                       */
/* created when either Data Server or the MetaDataWorks tool
                                                       */
/* uses the contents of an ESDT's INVENTORYMETADATA section in
                                                       */
/* order to generate an ESDT-specific MCF. The level of
/\star metadata coverage presented here corresponds to the metadata \star/
/* requirement for granules in Full Class as described in
                                                       */
/* Appendix B of DID 311 and Section 2.5 of the document 'BNF
/* Representation of the B.O Earth Science Data Model for the
                                                       */
/* ECS Project' {420-TP-016-001).
                                                       */
/*
                                                       */
/* This MCF file's contents were based on the ESDT Descriptor
  file template Ver-1.6, 3/31/97.
                                                       * /
/*
/*********************
GROUP = INVENTORYMETADATA
   GROUPTYPE = MASTERGROUP
/* ECSDataGranule */
   GROUP = ECSDataGranule
      /* Note: SizeMBECSDataGranule will be set by DSS, */
      /* not by the science software.
      OBJECT = SizeMBECSDataGranule
          Data Location = "DSS"
          NUM \overline{V}AL = 1
```

```
TYPE = "DOUBLE"
         Mandatory = "FALSE"
    END OBJECT = SizeMBECSDataGranule
    OBJECT = ReprocessingPlanned
         Data Location = "PGE"
         NUM \overline{V}AL = 1
         TYP\overline{E} = "STRING"
         Mandatory = "TRUE"
    END OBJECT = ReprocessingPlanned
    OBJECT = ReprocessingActual
         Data Location = "PGE"
         NUM \overline{V}AL = 1
         TYP\overline{E} = "STRING"
         Mandatory = "TRUE"
    END OBJECT = ReprocessingActual
    OBJECT = LocalGranuleID
         Data Location = "PGE"
         NUM \overline{V}AL = 1
         TYP\overline{E} = "STRING"
         Mandatory = "TRUE"
    END OBJECT = LocalGranuleID
    OBJECT = DayNightFlag
         Data Location = "PGE"
         NUM \overline{V}AL = 1
         TYP\overline{E} = "STRING"
         Mandatory = "TRUE"
    END OBJECT = DayNightFlag
    OBJECT = ProductionDateTime
         Data_Location = "TK"
         NUM VAL = 1
         TYP\overline{E} = "DATETIME"
         Mandatory = "TRUE"
    END OBJECT = ProductionDateTime
    OBJECT = LocalVersionID
         Data Location = "PGE"
         NUM \overline{V}AL = 1
         TYP\overline{E} = "STRING"
         Mandatory = "TRUE"
    END OBJECT = LocalVersionID
END GROUP = ECSDataGranule
GROUP = MeasuredParameter
    OBJECT = MeasuredParameterContainer
         Data Location = "NONE"
         Class = "M"
         Mandatory = "TRUE"
         OBJECT = ParameterName
```

```
Data Location = "PGE"
            Class = "M"
            TYPE = "STRING"
            NUM VAL = 1
            Mandatory = "TRUE"
        END OBJECT = ParameterName
GROUP = QAFlags
            Class = "M"
            OBJECT = AutomaticQualityFlag
                Data Location = "PGE"
                Mandatory = "TRUE"
                TYPE = "STRING"
                NUM VAL = 1
            END OBJECT = AutomaticQualityFlag
            OBJECT = AutomaticQualityFlagExplanation
                Data Location = "PGE"
                Mandatory = "TRUE"
                TYPE = "STRING"
                NUM VAL = 1
            END OBJECT = AutomaticQualityFlagExplanation
            OBJECT = OperationalQualityFlag
                Data Location = "DAAC"
                Mandatory = "FALSE"
                TYPE = "STRING"
                NUM VAL = 1
            END OBJECT = OperationalQualityFlag
            OBJECT = OperationalQualityFlagExplanation
                Data Location = "DAAC"
                Mandatory = "FALSE"
                TYPE = "STRING"
                NUM VAL = 1
            END OBJECT = OperationalQualityFlagExplanation
            OBJECT = ScienceQualityFlag
                Data Location = "DP"
                Mandatory = "FALSE"
                TYPE = "STRING"
                NUM VAL = 1
            END OBJECT = ScienceQualityFlag
            OBJECT = ScienceQualityFlagExplanation
                Data Location = "DP"
                Mandatory = "FALSE"
                TYPE = "STRING"
                NUM VAL = 1
            END OBJECT = ScienceQualityFlagExplanation
        END GROUP = QAFlags
           GROUP = QAStats
            Class = "M"
            OBJECT = QAPercentInterpolatedData
```

```
Data Location = "PGE"
                 NUM \overline{V}AL = 1
                 TYP\overline{E} = "INTEGER"
                 Mandatory = "TRUE"
             END OBJECT = QAPercentInterpolatedData
             OBJECT = QAPercentMissingData
                 Data Location = "PGE"
                 NUM \overline{V}AL = 1
                 TYP\overline{E} = "INTEGER"
                 Mandatory = "TRUE"
             END OBJECT = QAPercentMissingData
             OBJECT = QAPercentOutofBoundsData
                 Data Location = "PGE"
                 NUM_VAL = 1
                 TYPE = "INTEGER"
                 Mandatory = "TRUE"
             END_OBJECT = QAPercentOutofBoundsData
             OBJECT = QAPercentCloudCover
                 Data Location = "PGE"
                 NUM VAL = 1
                 TYPE = "INTEGER"
                 Mandatory = "TRUE"
             END OBJECT = QAPercentCloudCover
        \overline{\text{END GROUP}} = \overline{\text{QAStats}}
    END OBJECT = MeasuredParameterContainer
END GROUP = MeasuredParameter
GROUP = OrbitCalculatedSpatialDomain
    OBJECT = OrbitCalculatedSpatialDomainContainer
             Data Location = "NONE"
             Class = "M"
             Mandatory = "TRUE"
             OBJECT = OrbitalModelName
                 Data Location = "PGE"
                 Mandatory = "TRUE"
                 Class = "M"
                 TYPE = "STRING"
                 NUM_VAL = 1
             END OBJECT = OrbitalModelName
             OBJECT = OrbitNumber
                 Data Location = "PGE"
                 Mandatory = "TRUE"
                 Class = "M"
                 TYPE = "INTEGER"
                 NUM VAL = 1
             END OBJECT = OrbitNumber
             OBJECT = StartOrbitNumber
                 Data Location = "PGE"
                 Mandatory = "TRUE"
                 Class = "M"
```

7-11

```
TYPE = "INTEGER"
                NUM VAL = 1
            END OBJECT = StartOrbitNumber
            OBJECT = StopOrbitNumber
                Data Location = "PGE"
                Mandatory = "TRUE"
                Class = "M"
                TYPE = "INTEGER"
                NUM VAL = 1
            END OBJECT = StopOrbitNumber
            OBJECT = EquatorCrossingLongitude
                Data_Location = "PGE"
                Mandatory = "TRUE"
                Class = "M"
                TYPE = "DOUBLE"
                NUM VAL = 1
            END OBJECT = EquatorCrossingLongitude
            OBJECT = EquatorCrossingTime
                Data Location = "PGE"
                Mandatory = "TRUE"
                Class = "M"
                TYPE = "TIME"
                NUM VAL = 1
            END OBJECT = EquatorCrossingTime
            OBJECT = EquatorCrossingDate
                Data Location = "PGE"
                Mandatory = "TRUE"
                Class = "M"
                TYPE = "DATE"
                NUM VAL = 1
            END OBJECT = EquatorCrossingDate
    END OBJECT = OrbitCalculatedSpatialDomainContainer
END GROUP = OrbitCalculatedSpatialDomain
GROUP = CollectionDescriptionClass
    OBJECT = ShortName
        Data Location = "MCF"
        NUM \overline{V}AL = 1
        TYP\overline{E} = "STRING"
        Mandatory = "TRUE"
        Value = "L7ORF1"
    END OBJECT = ShortName
    OBJECT = VersionID
        Data Location = "MCF"
        NUM VAL = 1
        TYP\overline{E} = "STRING"
        Mandatory = "TRUE"
        Value = "1"
    END OBJECT = VersionID
```

```
END GROUP = CollectionDescriptionClass
    GROUP = SpatialDomainContainer
        GROUP = HorizontalSpatialDomainContainer
           /* ZoneIdentifierClass */
             GROUP = ZoneIdentifierClass
                  OBJECT = ZoneIdentifier
                      Data Location = "PGE"
                      NUM \overline{V}AL = 1
                      TYP\overline{E} = "STRING"
                      Mandatory = "TRUE"
                 END OBJECT = ZoneIdentifier
             \overline{\text{END GROUP}} = \overline{\text{ZoneIdentifierClass}}
           /* BoundingRectangle */
             GROUP = BoundingRectangle
                 OBJECT = WestBoundingCoordinate
                      Data Location = "PGE"
                      NUM \overline{V}AL = 1
                      TYPE = "DOUBLE"
                      Mandatory = "TRUE"
                  END OBJECT = WestBoundingCoordinate
                  OBJECT = NorthBoundingCoordinate
                      Data Location = "PGE"
                      NUM \overline{V}AL = 1
                      TYPE = "DOUBLE"
                      Mandatory = "TRUE"
                  END OBJECT = NorthBoundingCoordinate
                  OBJECT = EastBoundingCoordinate
                      Data_Location = "PGE"
                      NUM \overline{V}AL = 1
                      TYP\overline{E} = "DOUBLE"
                      Mandatory = "TRUE"
                  END OBJECT = EastBoundingCoordinate
                  OBJECT = SouthBoundingCoordinate
                      Data Location = "PGE"
                      NUM \overline{V}AL = 1
                      TYPE = "DOUBLE"
                      Mandatory = "TRUE"
                 END OBJECT = SouthBoundingCoordinate
             END GROUP = BoundingRectangle
         END GROUP = HorizontalSpatialDomainContainer
    END GROUP = SpatialDomainContainer
/* RangeDateTime */
    GROUP = RangeDateTime
         OBJECT = RangeBeginningTime
             Data Location = "PGE"
             NUM \overline{V}AL = 1
             TYP\overline{E} = "TIME"
```

7-13

```
Mandatory = "TRUE"
    END OBJECT = RangeBeginningTime
    OBJECT = RangeEndingTime
        Data Location = "PGE"
        NUM \overline{V}AL = 1
        TYP\overline{E} = "TIME"
        Mandatory = "TRUE"
    END OBJECT = RangeEndingTime
    OBJECT = RangeBeginningDate
        Data Location = "PGE"
        NUM \overline{V}AL = 1
        TYP\overline{E} = "DATE"
        Mandatory = "TRUE"
    END OBJECT = RangeBeginningDate
    OBJECT = RangeEndingDate
        Data Location = "PGE"
        NUM \overline{V}AL = 1
        TYP\overline{E} = "DATE"
        Mandatory = "TRUE"
    END OBJECT = RangeEndingDate
END_GROUP = RangeDateTime
GROUP = AdditionalAttributes
        OBJECT = AdditionalAttributesContainer
           Data Location = "NONE"
           Class = "M"
           Mandatory = "TRUE"
             /* AdditionalAttributes */
            OBJECT = AdditionalAttributeName
                 Data Location = "PGE"
                 Mandatory = "TRUE"
                 TYPE = "STRING"
                 Class = "M"
                 NUM VAL = 1
             END OBJECT = AdditionalAttributeName
             /* InformationContent */
             GROUP = InformationContent
                 Class = "M"
                 OBJECT = ParameterValue
                     Data Location = "PGE"
                     Mandatory = "TRUE"
                     TYPE = "STRING"
                     NUM VAL = 1
                 END OBJECT = ParameterValue
             END_GROUP = InformationContent
        END OBJECT = AdditionalAttributesContainer
```

```
END_GROUP = AdditionalAttributes
        GROUP = OrbitParametersGranule
            OBJECT = OrbitalParametersPointer
                 Data Location = "PGE"
                Mandatory = "TRUE"
                TYPE = "STRING"
                NUM VAL = 1
            END OBJECT = OrbitalParametersPointer
        END GROUP = OrbitParametersGranule
/* StorageMediumClass */
       GROUP = StorageMediumClass
            OBJECT = StorageMedium
                Data Location = "PGE"
                NUM_VAL = 10
                TYP\overline{E} = "STRING"
                Mandatory = "TRUE"
            END OBJECT = StorageMedium
        END GROUP = StorageMediumClass
END GROUP = INVENTORYMETADATA
GROUP = ARCHIVEDMETADATA
GROUPTYPE = MASTERGROUP
          /* BoundingRectangle */
            GROUP = BoundingRectangle
                 OBJECT = WestBoundingCoordinate
                     Data Location = "PGE"
                     NUM \overline{V}AL = 1
                     TYPE = "DOUBLE"
                     Mandatory = "TRUE"
                 END OBJECT = WestBoundingCoordinate
                 OBJECT = NorthBoundingCoordinate
                     Data_Location = "PGE"
                     NUM_VAL = 1
TYPE = "DOUBLE"
                     Mandatory = "TRUE"
                 END OBJECT = NorthBoundingCoordinate
                 OBJECT = EastBoundingCoordinate
                     Data Location = "PGE"
                     NUM \overline{V}AL = 1
                     TYPE = "DOUBLE"
                     Mandatory = "TRUE"
                 END OBJECT = EastBoundingCoordinate
                 OBJECT = SouthBoundingCoordinate
                     Data Location = "PGE"
                     NUM_VAL = 1
                     TYPE = "DOUBLE"
                     Mandatory = "TRUE"
```

7.4 The ODL Ouput File Which Results from Running Code in Section 7.2

```
/* */
/* This is a working version of the MCF template that will be */
/* supplied with the next SDP Toolkit. This MCF template will */
^{\prime \star} NOT be official until the SDP Toolkit is released. All ^{\star \prime}
/* details are subject to change. */
/* */
/\!\!\!\!\!^{\star} This MCF file represents the ODL which is expected to be ^{\star}/\!\!\!\!
/st created when either Data Server or the MetaDataWorks tool st/
/st uses the contents of an ESDT's INVENTORYMETADATA section in st/
^{\prime \star} order to generate an ESDT-specific MCF. The level of ^{\star}/
/* metadata coverage presented here corresponds to the metadata */
/* requirement for granules in Full Class as described in */
^{\prime \star} Appendix B of DID 311 and Section 2.5 of the document 'BNF ^{\star \prime}
/* Representation of the B.O Earth Science Data Model for the */
/* ECS Project' {420-TP-016-001). */
/* */
/* This MCF file's contents were based on the ESDT Descriptor */
/* file template Ver-1.6, 3/31/97. */
/* */
GROUP
                    = INVENTORYMETADATA
                   = MASTERGROUP
 GROUPTYPE
/* ECSDataGranule */
 GROUP
                    = ECSDATAGRANULE
   OBJECT
                      = REPROCESSINGPLANNED
    NUM VAL
                      = 1
                      = "ReprocessingplannINVENTR"
     VALUE
   END OBJECT
                       = REPROCESSINGPLANNED
   OBJECT
                       = REPROCESSINGACTUAL
                   = 1
= "Reprocessin"
= REPROCESSINGACTUAL
    NUM VAL
     VALUE
   END OBJECT
```

```
OBJECT
                    = LOCALGRANULEID
  NUM_VAL
VALUE
                     = 1
                     = "ID1111"
 END_OBJECT
                     = LOCALGRANULEID
 OBJECT
                     = DAYNIGHTFLAG
  NUM_VAL
                     = 1
   VALUE
                     = "Flag1"
 END OBJECT
                     = DAYNIGHTFLAG
 OBJECT
                    = PRODUCTIONDATETIME
  NUM VAL
                    = 1
   VALUE
                    = "1999-11-23T18:16:01.000Z"
 END OBJECT
                    = PRODUCTIONDATETIME
 OBJECT
                     = LOCALVERSIONID
   NUM_VAL
                    = "version1234"
   VALUE
 END OBJECT
                    = LOCALVERSIONID
                  = ECSDATAGRANULE
END GROUP
/* MeasuredParameter */
GROUP
                  = MEASUREDPARAMETER
 OBJECT
                     = MEASUREDPARAMETERCONTAINER
  CLASS
                     = "1"
   OBJECT
                      = PARAMETERNAME
                      = "1"
    CLASS
    NUM_VAL
                      = 1
                      = "information1"
    VALUE
   END_OBJECT
                      = PARAMETERNAME
   /* QAFlags */
   GROUP
                      = QAFLAGS
    CLASS
                      = "1"
     OBJECT
                        = AUTOMATICQUALITYFLAG
     NUM_VAL
                        = 1
                        = "1"
      CLASS
                       = "NOT SET"
      VALUE
     END OBJECT
                        = AUTOMATICQUALITYFLAG
     OBJECT
                        = AUTOMATICQUALITYFLAGEXPLANATION
      NUM VAL
                        = 1
                        = "1"
      CLASS
                        = "Exercise1"
      VALUE
     END OBJECT = AUTOMATICQUALITYFLAGEXPLANATION
   END GROUP
                      = QAFLAGS
```

```
/* QAStats */
 GROUP
                     = QASTATS
                     = "1"
   CLASS
   OBJECT
                       = QAPERCENTINTERPOLATEDDATA
    NUM VAL
                       = 1
    CLASS
                      = "1"
                       = 667788
    VALUE
   END_OBJECT
                      = QAPERCENTINTERPOLATEDDATA
   OBJECT
                      = QAPERCENTMISSINGDATA
    NUM_VAL
                      = 1
    CLASS
                      = "1"
                       = 12345
    VALUE
   END OBJECT
                       = QAPERCENTMISSINGDATA
                       = QAPERCENTOUTOFBOUNDSDATA
   OBJECT
    NUM_VAL
                       = 1
                       = "1"
     CLASS
                       = 123
    VALUE
   END OBJECT
                      = QAPERCENTOUTOFBOUNDSDATA
   OBJECT
                      = QAPERCENTCLOUDCOVER
     NUM_VAL
                      = 1
                      = "1"
    CLASS
                      = "NOT SET"
    VALUE
   END_OBJECT
                       = QAPERCENTCLOUDCOVER
                    = QASTATS
 END_GROUP
                   = MEASUREDPARAMETERCONTAINER
END OBJECT
OBJECT
                    = MEASUREDPARAMETERCONTAINER
                    = "2"
 CLASS
 OBJECT
                     = PARAMETERNAME
  CLASS
                    = "2"
  NUM_VAL
                     = 1
   VALUE
                    = "information2"
 END OBJECT
                     = PARAMETERNAME
 /* QAFlags */
 GROUP
                    = QAFLAGS
                     = "2"
   CLASS
   OBJECT
                      = AUTOMATICQUALITYFLAG
    NUM VAL
                      = 1
                      = "2"
    CLASS
                      = "NOT SET"
    VALUE
   END OBJECT
                      = AUTOMATICQUALITYFLAG
   OBJECT
                      = AUTOMATICQUALITYFLAGEXPLANATION
     NUM VAL
                       = 1
```

```
CLASS
VALUE
END_OBJECT
                       = "2"
                      = "NOT SET"
                       = AUTOMATICQUALITYFLAGEXPLANATION
 END GROUP
                      = QAFLAGS
 /* QAStats */
 GROUP
                     = QASTATS
                     = "2"
   CLASS
   OBJECT
                       = QAPERCENTINTERPOLATEDDATA
    NUM_VAL
CLASS
VALUE
                       = 1
                       = "2"
                       = "NOT SET"
    VALUE
   END OBJECT
                       = QAPERCENTINTERPOLATEDDATA
   OBJECT
                       = QAPERCENTMISSINGDATA
    NUM_VAL
                       = 1
     CLASS
                       = "2"
                       = 56789
    VALUE
   END OBJECT
                       = QAPERCENTMISSINGDATA
   OBJECT
                       = QAPERCENTOUTOFBOUNDSDATA
    NUM_VAL
                       = 1
                       = "2"
     CLASS
                       = 23456
    VALUE
   END_OBJECT
                       = QAPERCENTOUTOFBOUNDSDATA
   OBJECT
                       = QAPERCENTCLOUDCOVER
    NUM VAL
                       = 1
    CLASS
                       = "2"
                       = "NOT SET"
     VALUE
   END OBJECT
                       = QAPERCENTCLOUDCOVER
 END_GROUP
                     = QASTATS
END OBJECT
                    = MEASUREDPARAMETERCONTAINER
OBJECT
                    = MEASUREDPARAMETERCONTAINER
                    = "3"
 CLASS
 OBJECT
                     = PARAMETERNAME
  CLASS
                     = "3"
  NUM_VAL
                     = 1
                     = "information3"
   VALUE
 END OBJECT
                     = PARAMETERNAME
 /* QAFlags */
                    = QAFLAGS
= "3"
 GROUP
   CLASS
   OBJECT
                       = AUTOMATICQUALITYFLAG
     NUM VAL
                       = 1
```

```
= "3"
     CLASS
    VALUE
                      = "NOT SET"
   END OBJECT
                      = AUTOMATICQUALITYFLAG
   OBJECT
                       = AUTOMATICQUALITYFLAGEXPLANATION
    NUM_VAL
                      = "3"
    CLASS
VALUE
                      = "NOT SET"
   END_OBJECT
                      = AUTOMATICQUALITYFLAGEXPLANATION
 END GROUP
                    = QAFLAGS
 /* QAStats */
 GROUP
                     = QASTATS
   CLASS
                     = "3"
   OBJECT
                      = QAPERCENTINTERPOLATEDDATA
    NUM_VAL
                      = 1
                      = "3"
    CLASS
                      = "NOT SET"
    VALUE
   END OBJECT
                      = QAPERCENTINTERPOLATEDDATA
   OBJECT
                      = QAPERCENTMISSINGDATA
    NUM_VAL
                      = 1
                      = "3"
    CLASS
                      = "NOT SET"
    VALUE
   END_OBJECT
                      = QAPERCENTMISSINGDATA
                      = QAPERCENTOUTOFBOUNDSDATA
   OBJECT
    NUM VAL
                      = 1
    CLASS
                      = "3"
                      = "NOT SET"
    VALUE
   END_OBJECT
                      = QAPERCENTOUTOFBOUNDSDATA
   OBJECT
                      = QAPERCENTCLOUDCOVER
    NUM_VAL
                      = 1
                      = "3"
     CLASS
                      = "NOT SET"
    VALUE
   END OBJECT
                       = QAPERCENTCLOUDCOVER
 END_GROUP
                     = QASTATS
END OBJECT
                   = MEASUREDPARAMETERCONTAINER
OBJECT
                   = MEASUREDPARAMETERCONTAINER
 CLASS
                   = "4"
 OBJECT
                    = PARAMETERNAME
  CLASS
                    = "4"
  NUM_VAL
                     = 1
                    = "information4"
  VALUE
 END OBJECT
                     = PARAMETERNAME
 /* QAFlags */
```

```
GROUP
CLASS
                        = QAFLAGS
                        = "4"
     OBJECT
                           = AUTOMATICQUALITYFLAG
       NUM VAL
       CLASS
                          = "4"
      VALUE
                          = "NOT SET"
     END_OBJECT
                          = AUTOMATICQUALITYFLAG
     OBJECT
                         = AUTOMATICQUALITYFLAGEXPLANATION
       NUM VAL
                         = 1
       CLASS
VALUE
                          = "4"
                         = "NOT SET"
     END OBJECT
                          = AUTOMATICQUALITYFLAGEXPLANATION
   END_GROUP
                        = QAFLAGS
   /* QAStats */
   GROUP
                       = QASTATS
                        = "4"
     CLASS
     OBJECT
                         = QAPERCENTINTERPOLATEDDATA
       NUM VAL
                         = 1
                          = "4"
       CLASS
                          = "NOT SET"
      VALUE
     END_OBJECT
                          = QAPERCENTINTERPOLATEDDATA
     OBJECT
                          = QAPERCENTMISSINGDATA
       NUM VAL
                          = 1
       CLASS
                          = "4"
                          = "NOT SET"
      VALUE
                          = QAPERCENTMISSINGDATA
     END OBJECT
     OBJECT
                          = QAPERCENTOUTOFBOUNDSDATA
      NUM_VAL
                          = 1
                          = "4"
       CLASS
                          = "NOT SET"
      VALUE
     END OBJECT
                          = QAPERCENTOUTOFBOUNDSDATA
     OBJECT
                          = QAPERCENTCLOUDCOVER
      NUM_VAL
                          = 1
                          = "4"
       CLASS
                          = "NOT SET"
       VALUE
     END OBJECT
                          = QAPERCENTCLOUDCOVER
   END_GROUP
                       = QASTATS
 END OBJECT
                      = MEASUREDPARAMETERCONTAINER
END_GROUP
                     = MEASUREDPARAMETER
GROUP
                     = ORBITCALCULATEDSPATIALDOMAIN
 OBJECT
                       = ORBITCALCULATEDSPATIALDOMAINCONTAINER
```

```
CLASS
                     = "M"
   OBJECT
                       = ORBITALMODELNAME
    CLASS
                       = "M"
    NUM_VAL
                       = 1
   VALUE = "NOT SET"
END_OBJECT = ORBITALMODELNAME
   OBJECT
                      = ORBITNUMBER
                       = "M"
    CLASS
    NUM VAL
                       = 1
    VALUE
                      = "NOT SET"
                      = ORBITNUMBER
   END OBJECT
   OBJECT
                       = STARTORBITNUMBER
    CLASS
                       = "M"
    NUM_VAL
                       = 1
                       = "NOT SET"
     VALUE
                       = STARTORBITNUMBER
   END OBJECT
   OBJECT
                      = STOPORBITNUMBER
    CLASS
                       = "M"
    NUM VAL
                      = 1
    VALUE
                      = "NOT SET"
   END OBJECT
                      = STOPORBITNUMBER
                     = EQUATORCROSSINGLONGITUDE
= "M"
   OBJECT
    CLASS
    NUM_VAL
                       = 1
   VALUE = "NOT SET"
END_OBJECT = EQUATORCROSSINGLONGITUDE
   OBJECT
                      = EQUATORCROSSINGTIME
                       = "M"
    CLASS
                       = 1
    NUM_VAL
                      = "NOT SET"
= EQUATORCROSSINGTIME
    VALUE
   END_OBJECT
   OBJECT
                       = EQUATORCROSSINGDATE
                       = "M"
    CLASS
    NUM_VAL
                        = 1
                       = "NOT SET"
     VALUE
   END OBJECT
                       = EQUATORCROSSINGDATE
 END OBJECT
                     = ORBITCALCULATEDSPATIALDOMAINCONTAINER
END GROUP
                   = ORBITCALCULATEDSPATIALDOMAIN
/* CollectionDescriptionClass */
GROUP
                    = COLLECTIONDESCRIPTIONCLASS
 OBJECT
                      = SHORTNAME
   NUM VAL
                      = 1
                    = "L70RF1"
   VALUE
             = SHORTNAME
 END OBJECT
```

```
OBJECT
                     = VERSIONID
   NUM_VAL
                     = 1
                     = "1"
   VALUE
 END_OBJECT
                      = VERSIONID
                   = COLLECTIONDESCRIPTIONCLASS
END_GROUP
/* SpatialDomainContainer */
GROUP
                    = SPATIALDOMAINCONTAINER
 GROUP
                      = HORIZONTALSPATIALDOMAINCONTAINER
   /* ZoneIdentifierClass */
   GROUP
                       = ZONEIDENTIFIERCLASS
     OBJECT
                         = ZONEIDENTIFIER
      NUM_VAL
                         = 1
                         = "NOT SET"
      VALUE
     END OBJECT
                         = ZONEIDENTIFIER
   END GROUP
                 = ZONEIDENTIFIERCLASS
   /* BoundingRectangle */
   GROUP
                       = BOUNDINGRECTANGLE
     OBJECT
                          = WESTBOUNDINGCOORDINATE
                          = 1
      NUM VAL
                         = 11.110000
      VALUE
     END OBJECT
                         = WESTBOUNDINGCOORDINATE
     OBJECT
                         = NORTHBOUNDINGCOORDINATE
      NUM_VAL
                         = 1
                         = 22.220000
       VALUE
     END OBJECT
                          = NORTHBOUNDINGCOORDINATE
     OBJECT
                          = EASTBOUNDINGCOORDINATE
      NUM VAL
                          = 1
       VALŪE
                         = 33.330000
     END OBJECT
                         = EASTBOUNDINGCOORDINATE
     OBJECT
                         = SOUTHBOUNDINGCOORDINATE
       NUM VAL
                         = 1
       VALUE
                          = 44.440000
     END OBJECT
                         = SOUTHBOUNDINGCOORDINATE
   END GROUP
                       = BOUNDINGRECTANGLE
 END_GROUP
                    = HORIZONTALSPATIALDOMAINCONTAINER
END GROUP
                   = SPATIALDOMAINCONTAINER
```

```
/* RangeDateTime */
 GROUP
                      = RANGEDATETIME
   OBJECT
                         = RANGEBEGINNINGTIME
     NUM_VAL
                         = 1
     VALŪE
                         = "NOT SET"
   END OBJECT
                         = RANGEBEGINNINGTIME
   OBJECT
                         = RANGEENDINGTIME
     NUM VAL
                         = 1
                         = "NOT SET"
     VALUE
   END OBJECT
                        = RANGEENDINGTIME
   OBJECT
                         = RANGEBEGINNINGDATE
     NUM_VAL
                         = "1997.07/30"
     VALUE
   END OBJECT
                         = RANGEBEGINNINGDATE
   OBJECT
                         = RANGEENDINGDATE
     NUM VAL
                       = 1
     VALUE
                       = "NOT SET"
   END_OBJECT
                        = RANGEENDINGDATE
 END GROUP
                      = RANGEDATETIME
 GROUP
                      = ADDITIONALATTRIBUTES
   OBJECT
                         = ADDITIONALATTRIBUTESCONTAINER
     CLASS
     /* AdditionalAttributes */
     OBJECT
                          = ADDITIONALATTRIBUTENAME
      CLASS
                          = "M"
      NUM_VAL
                          = 1
                          = "NOT SET"
      VALUE
                          = ADDITIONALATTRIBUTENAME
     END OBJECT
     /* InformationContent */
     GROUP
                           = INFORMATIONCONTENT
                           = "M"
       CLASS
       OBJECT
                           = PARAMETERVALUE
         NUM VAL
                           = 1
       CLASS = M
VALUE = "NOT SET"
END_OBJECT = PARAMETERVALUE
     END GROUP
                         = INFORMATIONCONTENT
   END_OBJECT
                        = ADDITIONALATTRIBUTESCONTAINER
```

```
END GROUP
                         = ADDITIONALATTRIBUTES
    GROUP
                            = ORBITPARAMETERSGRANULE
    OBJECT
                            = ORBITALPARAMETERSPOINTER
      NUM VAL
                            = 1
                            = "NOT SET"
      VALUE
    END OBJECT
                            = ORBITALPARAMETERSPOINTER
  END GROUP
                          = ORBITPARAMETERSGRANULE
    GROUP
                            = STORAGEMEDIUMCLASS
    OBJECT
                            = STORAGEMEDIUM
      NUM VAL
      VALUE
                            = "NOT SET"
    END OBJECT
                            = STORAGEMEDIUM
  END GROUP
                         = STORAGEMEDIUMCLASS
END GROUP
                        = INVENTORYMETADATA
END
```

7.5 The file filetable.temp used for example in Section 7.2

```
# This file is needed for testing TIME tools. Only the Path for the files need to be changed.
# The following IDs are defined in the TOOLKIT and they SHOULD NOT be changed
10100|LogStatus|/tk/TOOLKIT_MTD/test/test_MET_HDF5/LogStatus 5000|configfile.dat|/tk/TOOLKIT_MTD/runtime/configfile.dat
10252|GetAttrtemp|/tk/TOOLKIT_MTD/test/test_MET_HDF5/GetAttrtemp
10254|MCFWrite.temp|/tk/TOOLKIT MTD/test/test MET HDF5/MCFWrite.temp
10255|AsciiDump|/tk/TOOLKIT MTD/test/test MET HDF5/AsciiDump
10256|temporary.MCF|/tk/TOOLKIT MTD/test/test MET HDF5/temporary.MCF
10301|leapsec.dat|/tk/TOOLKIT MTD/database/common/TD/leapsec.dat
10401|utcpole.dat|/tk/TOOLKIT MTD/database/common/CSC/utcpole.dat
10402|earthfigure.dat|/tk/TOOLKIT MTD/database/common/CSC/earthfigure.dat
10601|de200.eos|/tk/TOOLKIT_MTD/database/common/CBP/de200.eos
10801|sc_tags.dat|/tk/TOOLKIT_MTD/database/common/EPH/sc_tags.dat 10302|udunits.dat|/tk/TOOLKIT_MTD/database/common/CUC/udunits.dat
# Logical IDs assigned for input/output files can be changed BUT they
# should be diffrent from the IDs assigned above.
10250|MCF File|/tk/TOOLKIT MTD/test/test MET HDF5/MET TestData/MCF File
10251|data dict|/tk/TOOLKIT MTD/test/test MET HDF5/MET TestData/data dict
5039|Swath h5.hdf|/tk/TOOLKIT MTD/test/fest MET HDF5/MET TestData/Swath h5.hdf
# files to check PGS MET InitNonMCF function
```

Appendix A. Installation and Maintenance

A.1 Installation Procedures

A.1.1 Preliminary Step

Before installing HDFEOS, you must already have installed NCSA HDF, Version 5-1.2.0 on your host. The installation script will prompt for the paths to the HDF include and library directories. Please see the SDP Toolkit Users Guide for the ECS Project, Section 5 for instructions on installing both the Toolkit and HDF. See also: http://hdf.ncsa.uiuc.edu/ for instructions on how to access HDF libraries.

A.1.2 Unpacking the Distribution File

- 1) Select a location for the HDFEOS directory tree. Installing HDFEOS alone requires a disk partition with at least 25 Mb of free space.
- 2) Copy the file HDF-EOSv3.0.tar.Z to the target directory by

```
typing the command:
cp HDF-EOSv3.0.tar.Z <target-dir>
where <target-dir> is the full pathname of your target directory.
```

3) Set your default directory to the target directory by typing the command:

```
cd <target-dir>
```

4) Uncompress this file and extract the contents by typing the command:

```
zcat HDF-EOSv3.0.tar.Z | tar xvf -
```

This will create a subdirectory of the current directory called 'hdfeos'. This is the top-level HDFEOS directory, which contains the full HDFEOS directory structure.

A.1.3 Starting the Installation Procedure

- 1) Set your default directory to the top-level HDFEOS directory by typing the command: cd hdfeos
- 2) Select installation options.

Currently, the only options are those specific to the SGI Power Challenge platform.

On the SGI Challenge, the *default* is to build HDFEOS in 64-bit mode, which is the same as the Toolkit. The following table gives the option to specify the appropriate architecture to be built:

binary format	architecture	<install-options></install-options>
new 32-bit	sgi32	-sgi32
64 bit	sgi64	-sgi64

Please note that the old-32-bit mode has been dropped as the default because it is no longer being supported by SGI, it is therefore recommended that all users migrate to new-style 32 bit or 64 bit mode.

3) Run the installation script.

Please note that the installation script for this release of HDFEOS requires user interaction. Because of this, it should NOT be run as a background task.

3.0) If you wish to generate a log of this session, use the Unix 'script' command. This command runs a sub-shell that saves all terminal output to the specified file. To log the session, type:

```
script <logfile-name>
```

where <logfile-name> is the name of the log file

3.1) To run the installation script, type the command:

```
bin/INSTALL-HDFEOS <install-options>
```

where <install-options> is the list of options determined in the previous step.

The installation script will then run. It will output various startup messages, beginning with:

HDFEOS installation starting at <date/time

3.2) Enter the full pathnames for the hdf5-1.2.0 library and include directory paths, when the script prompts for them. If there is an error in the supplied paths, the script will exit.

NOTE: If the environment variables HDFLIB and/or HDFINC are set in your shell, the script will use these for the default values. If this is not the first run of the script, the default values will be taken from the values used for the last run of the script. In either of these cases, the installation script will prompt with:

```
Current value of the HDF library directory is: <path> Accept [y]/n: and/or Current value of the HDF include directory is: <path> Accept [y]/n:
```

Make sure to type 'n' and hit return, if the defaults do not point to the correct directories. The script will then prompt for the new values.

3.3) The installation script will finish with the following message:

HDFEOS installation ending at <date/time>

3.4) (optional - see 3.0)

If you ran the Unix 'script' command to create a log file, then type 'exit' and hit return at the command prompt. This will exit the sub-shell stated by 'script' and save the log file.

Hint: The log file generated by the script command may contain 'hard return' characters at the end of each line. These appear in some text editors as "^M". They can be removed with the following command:

```
sed 's/.$//' <logfile-name> > <logfile-name>.new where <logfile-name> is the name of the log file.
```

A.1.4 User Account Setup

Once HDFEOS has been installed, the accounts of HDFEOS users must be set up to define environment variables needed to compile and run code with HDFEOS (see parts 2 and 3 of the Notes section, below). The type of setup depends on the user's login shell.

1A) C shell (csh) Users:

Edit the HDFEOS user's .cshrc file to include the following line:

```
source <HDFEOS-home-dir>/bin/$BRAND/hdfeos_env.csh
```

where <HDFEOS-home-dir> is the full path of the HDFEOS home directory, and \$BRAND is an architecture-specific value for your host. Please refer to part 2 of the Notes section, below, to determine the correct value.

The script hdfeos_env.csh sets up all the variables discussed in parts 2 and 3 of the Notes section, below, and it adds the HDFEOS bin directory to the user path.

The environment variables will become available during all subsequent login sessions. To activate them for the current session, simply type one of the two lines listed above, at the Unix prompt.

Note regarding path setup with hdfeos_env.csh:

The script hdfeos_env.csh also makes available a variable called hdfeos_path. This can be added to the user's path to ensure that it accesses the directories necessary for the compilers and other utilities used to generate executable programs. It is not added to the user path by default, because in many cases it adds unnecessary complexity to the user path. To add hdfeos_path to the user path, modify the HDFEOS user's .cshrc file to include the following:

```
set my_path = ($path) # save path
source <HDFEOS-HOME-DIR>/bin/$BRAND/hdfeos_env.csh # HDFEOS setup
set path = ($my_path $hdfeos_path) # add hdfeos_path
```

INSTEAD OF the line listed at the beginning of this step.

Note that it is the user's responsibility to set up his or her own path so that it doesn't duplicate the directories set up in hdfeos_path. Please also note that the hdfeos_path is added AFTER the user's path. This way, the user's directories will be searched first when running Unix commands.

1B) Korn shell (ksh) Users:

Edit the HDFEOS user's .profile file to include the following line:

. <HDFEOS-home-dir>/bin/\$BRAND/hdfeos_env.ksh

where <HDFEOS-home-dir> is the full path of the HDFEOS home directory, and \$BRAND is an architecture-specific value for your host. Please refer to part 2 of the Notes section, below, to determine the correct value.

The script hdfeos_env.ksh sets up all the variables discussed in part 2 and 3 of the Notes section, below, and it adds the HDFEOS bin directory to the user path.

The environment variables will become available during all subsequent login sessions. To activate them for the current session, simply type one of the two lines listed above, at the Unix prompt.

Note regarding path setup with hdfeos env.ksh:

The script hdfeos_env.ksh also makes available a variable called hdfeos_path. This can be added to the user's path to ensure that it accesses the directories necessary for the compilers and other utilities used to generate executable programs. It is not added to the user path by default, because in many cases it adds unnecessary complexity to the user path. To add hdfeos_path to the user path, modify the HDFEOS user's .profile file to include the following:

```
my_path="$PATH" # save path . <HDFEOS-HOME-DIR>/bin/$BRAND/hdfeos_env.ksh # HDFEOS setup PATH="$my_path:$hdfeos_path"; export PATH # add hdfeos_path
```

INSTEAD OF the line listed at the beginning of this step.

Note that it is the user's responsibility to set up his or her own path so that it doesn't duplicate the directories set up in hdfeos_path. Please also note that the hdfeos_path is added AFTER the user's path. This way, the user's directories will be searched first when running Unix commands.

1C) Bourne shell (sh) Users:

Set up the required HDFEOS environment variables by appending the contents of the file <HDFEOS-home-dir>/bin/\$BRAND/hdfeos_env.ksh to the end of the HDFEOS user's .profile, where <HDFEOS-home-dir> is the full path of the HDFEOS home directory, and \$BRAND is an architecture-specific value for your host. Please refer to part 2 of the Notes section, below, to determine the correct value.

The environment variables will become available during all subsequent login sessions. To activate them, log out and then log back in.

A.1.5 File Cleanup

Once HDFEOS has been built and tested, you can delete certain temporary files and directories to save some disk space. Note that once these files have been removed, you will need to unpack the original distribution file in order to re-do the installation.

To remove these files:

```
cd <HDFEOS-home-dir>/bin
rm -rf tmp
cd <HDFEOS-home-dir>/lib
rm -rf tmp
```

A.1.6 Compiling and Linking with HDFEOS

In order to compile and link programs with the HDFEOS you must access the HDFEOS include and library files. To do this be sure that your makefiles include something like the following:

```
INCLUDE = -I. -I$(HDFEOS_INC) -I$(HDFINC)
LIBRARY = -L. -L$(HDFEOS_LIB) -L$(HDFLIB)
LDFLAGS = -lhdfeos -lGctp -lhdf -lnsl -lm (Sun platform)
LDFLAGS = -lhdfeos -lGctp -lhdf -lm (others)
```

The environment variables HDFEOS_INC, HDFEOS_LIB, HDFINC and HDFLIB are set up by the HDFEOS environment scripts (see User Setup, above). The refer to the include and library directories for HDFEOS and HDF, respectively.

The INCLUDE macro should be included in all compilation statements. The LIBRARY an LDFLAGS macros should be included in all link statements.

A.2 Notes

1) Approved Platforms

HDFEOS was built and tested in a multi-platform environment. The list of approved platforms, which includes information about operating system and compiler versions, may be found in the HDFEOS User's Guide and is also listed below.

Platform	os	Version	C Compiler	FORTRAN77
Sun Sparc	Solaris	2.5.1	Sun C 4.0	Sun FORTRAN 4.0
SGI Power Challenge	IRIX	6.2	SGI C 7.0	SGI FORTRAN 7.0

Note: The compilers are supplied by the vendor. The SGI Power Challenge (64-bit mode) had the native SGI FORTRAN 90 7.0.

2) Architecture Type Names

To track architecture dependencies, HDFEOS defines the environment variable \$BRAND. Following is a list of valid values for this variable, which is referred to throughout this document:

<u>\$BRAND</u> <u>Architecture</u>

sgi64 SGI Power Challenge (64-bit mode)

sun5 Sun: SunOS 5.x

3) Directory and File Environment Variables

In order to use the HDFEOS library and utilities, a number of environment variables MUST be set up to point to HDFEOS directories and files. These variables are automatically set up in User Account Setup section of the installation instructions. They are listed here for reference:

name	value	description		
HDFEOS_HOME	<install-path>/hdfeos</install-path>	top-level directory		
(where <install-path> is the absolute directory path above hdfeos)</install-path>				
HDFEOS_BIN	\$HDFEOS_HOME/bin/\$BRAND	executable files		
HDFEOS_INC	\$HDFEOS_HOME/include	header files		
HDFEOS_LIB	HDFEOS_HOME/lib/\$BRAND	library files		
HDFEOS_OBJ	\$HDFEOS_HOME/obj/\$BRAND	object files		
HDFEOS_SRC	\$HDFEOS_HOME/src	source files		

4) Other Environment Variables

In addition, the makefiles which are used to build the library require certain machine-specific environment variables. These set compilers, compilation flags and libraries, allowing a single set of makefiles to serve on multiple platforms. The User Account Setup section of the installation instructions explains how to set them up. They are listed here for reference:

<u>name</u>	description
CC	C compiler
CFLAGS	default C flags (optimize, ANSI)
C_CFH	C w/ cfortran.h callable from FORTRAN
CFHFLAGS	CFLAGS + C_CFH
C_F77_CFH	C w/ cfortran.h calling FORTRAN
C_F77_LIB	FORTRAN lib called by C main
F77	FORTRAN compiler
F77FLAGS	common FORTRAN flags
F77_CFH	FORTRAN callable from C w/ cfortran.h
F77_C_CFH	FORTRAN calling C w/ cfortran.h
CFH_F77	same as F77_C_CFH
F77_C_LIB	C lib called by FORTRAN main

5) Tools Provided with This Release

For a complete list of the tools provided with this release of HDFEOS, please refer to Section 7 of this document.

6) Copyright Notice for cfortran.h

HDFEOS functions are written in C. These C-based tools include the file cfortran.h, using it to generate machine-independent FORTRAN bindings. The cfortran.h facility includes the following notice which must accompany distributions that use it:

THIS PACKAGE, I.E. CFORTRAN.H, THIS DOCUMENT, AND THE CFORTRAN.H EXAMPLEPROGRAMS ARE PROPERTY OF THE AUTHOR WHO RESERVES ALL RIGHTS. THIS PACKAGE ANDTHE CODE IT PRODUCES MAY BE FREELY DISTRIBUTED WITHOUT FEES, SUBJECT TO THEFOLLOWING RESTRICTIONS:

- YOU MUST ACCOMPANY ANY COPIES OR DISTRIBUTION WITH THIS (UNALTERED) NOTICE.
- YOU MAY NOT RECEIVE MONEY FOR THE DISTRIBUTION OR FOR ITS MEDIA (E.G. TAPE, DISK, COMPUTER, PAPER.)
- YOU MAY NOT PREVENT OTHERS FROM COPYING IT FREELY.
- YOU MAY NOT DISTRIBUTE MODIFIED VERSIONS WITHOUT CLEARLY DOCUMENTING YOUR
- CHANGES AND NOTIFYING THE AUTHOR.
- YOU MAY NOT MISREPRESENTED THE ORIGIN OF THIS SOFTWARE, EITHER BY EXPLICIT CLAIM OR BY OMISSION.

THE INTENT OF THE ABOVE TERMS IS TO ENSURE THAT THE CFORTRAN.H PACKAGE NOT BEUSED FOR PROFIT MAKING ACTIVITIES UNLESS SOME ROYALTY ARRANGEMENT IS ENTERED INTO WITH ITS AUTHOR.

THIS SOFTWARE IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE SOFTWARE IS WITH YOU. SHOULD THE SOFTWARE PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION. THE AUTHOR IS NOT RESPONSIBLE FOR ANY SUPPORT OR SERVICE OF THE CFORTRAN.H PACKAGE.

Burkhard Burow

burow@vxdesy.cern.ch

A.3 Test Drivers

Also included with this software delivery is a tar file containing test driver programs.

These test programs are provided to aid the user in the development of software using the HDF-EOS library. The user may run the same test cases as included in this file to verify that the

software is functioning correctly. These programs were written to support the internal testing and are not an official part of the delivery. Users make use of them at their own risk. No support will be provided to the user of these programs. The tar file contains source code for a drivers in C and FORTRAN for each tool; sample output files; and input files and/or shell scripts, where applicable.

The UNIX command: "zcat HDF-EOS3.0v1.00_ TestDrivers.tar.Z | tar xvf" will create a directory called test_drivers beneath the current directory containing all these test files

A.4 User Feedback Mechanism

The mechanism for handling user feedback, documentation and software discrepancies, and bug reports follows:

- 1) The following accounts at the ECS Landover facility have been set up for user response:
 - pgstlkit@eos.hitc.com and
 - hdfeos@eos.hitc.com
- 2) Users will e-mail problem reports and comments to the above account. A receipt will be returned to the sender. A workoff plan for the discrepancy will be developed and status report issued once a month. Responses will be prioritized based on the severity of the problem and the available resources. Simple bug fixes will be turned around sooner, while requested functional enhancements to the Toolkit will be placed in a recommended requirements data base (RRDB) and handled more formally.
- 3) In order to help expedite responses, we request the following information be supplied with problem reports:
 - Name:
 - Date:
 - EOS Affiliation (DAAC, Instrument, Earth Science Data and Information System (ESDIS), etc.):
 - Phone No.:
 - Development Environment:
 - Computing Platform:
 - Operating System:
 - Compiler and Compiler Flags:
 - Tool Name:
 - Problem Description:

(Please include exact inputs to and outputs from the toolkit call, including error code returned by the function, plus exact error message returned where applicable.)

Suggested Resolution (include code fixes or workarounds if applicable):

4) In addition to the email response mechanism, a phone answering machine is also provided. The telephone number is: 301–925–0781. Calls will be returned as soon as possible. We note, however, that email is our preferred method of responding to users.

This page intentionally left blank.

Abbreviations and Acronyms

AI&T algorithm integration & test

AIRS Atmospheric Infrared Sounder

API application program interface

ASTER Advanced Spaceborne Thermal Emission and Reflection Radiometer

CCSDS Consultative Committee on Space Data Systems

CDRL Contract Data Requirements List

CDS CCSDS day segmented time code

CERES Clouds and Earth Radiant Energy System

CM configuration management

COTS commercial off-the-shelf software

CUC constant and unit conversions

CUC CCSDS unsegmented time code

DAAC distributed active archive center

DBMS database management system

DCE distributed computing environment

DCW Digital Chart of the World

DEM digital elevation model

DTM digital terrain model

ECR Earth centered rotating

ECS EOSDIS Core System

EDC Earth Resources Observation Systems (EROS) Data Center

EDHS ECS Data Handling System

EDOS EOSDIS Data and Operations System

EOS Earth Observing System

EOSAM EOS AM Project (morning spacecraft series)

EOSDIS Earth Observing System Data and Information System

EOSPM EOS PM Project (afternoon spacecraft series)

ESDIS Earth Science Data and Information System (GSFC Code 505)

FDF flight dynamics facility

FOV field of view

ftp file transfer protocol

GCT geo-coordinate transformation

GCTP general cartographic transformation package

GD grid

GPS Global Positioning System

GSFC Goddard Space Flight Center

HDF hierarchical data format

HITC Hughes Information Technology Corporation

http hypertext transport protocol

I&T integration & test

ICD interface control document

IDL interactive data language

IP Internet protocol

IWG Investigator Working Group

JPL Jet Propulsion Laboratory

LaRC Langley Research Center

LIS Lightening Imaging Sensor

M&O maintenance and operations

MCF metadata configuration file

MET metadata

MODIS Moderate–Resolution Imaging Spectroradiometer

MSFC Marshall Space Flight Center

NASA National Aeronautics and Space Administration

NCSA National Center for Supercomputer Applications

netCDF network common data format

NGDC National Geophysical Data Center

NMC National Meteorological Center (NOAA)

ODL object description language

PC process control

PCF process control file

PDPS planning & data production system

PGE product generation executive (formerly product generation executable)

POSIX Portable Operating System Interface for Computer Environments

PT point

QA quality assurance

RDBMS relational data base management system

RPC remote procedure call

RRDB recommended requirements database

SCF Science Computing Facility

SDP science data production

SDPF science data processing facility

SGI Silicon Graphics Incorporated

SMF status message file

SMP Symmetric Multi–Processing

SOM Space Oblique Mercator

SPSO Science Processing Support Office

SSM/I Special Sensor for Microwave/Imaging

SW swath

TAI International Atomic Time

TBD to be determined

TDRSS Tracking and Data Relay Satellite System

TRMM Tropical Rainfall Measuring Mission (joint US – Japan)

UARS Upper Atmosphere Research Satellite

UCAR University Corporation for Atmospheric Research

URL universal reference locator

USNO United States Naval Observatory

UT universal time

UTC Coordinated Universal Time

UTCF universal time correlation factor

UTM universal transverse mercator

VPF vector product format

WWW World Wide Web